


A large, bold, red geometric graphic on the left side of the page, consisting of several rectangular blocks of varying sizes arranged in a stepped, L-like shape.

PRODUCT CATALOGUE

From **nanometer** to **hectometer**
we provide professional precision measurement solutions



Since established in 2002, Chotest Technology Inc. is focusing on the designing and manufacturing of precision dimensional measurement and calibration instruments.

With more than decade professional technology accumulation, Chotest has accumulated rich practical experience and set up a strong team who is specialized in optics, machinery, electronics and information technology. At present, CHOTEST has more than 100 technology patents and software intellectual property rights. With competence in Micro-Nano motion, 3D Reconstruction of Micro-Nano

Quality and Service is Our Standard



measurement, 3D Form and Surface Analysis of Micro-Nano measurement, Large-scale 3D Measurement, Precision Sensing Probe and Image processing technology, Chotest is capable to provide the customers with professional precision measurement solution in domains from Nanometer to Hectometer.

Our products are widely used by public metrology labs and quality inspection workshops in the automotive, aerospace, machinery, metallurgy, power, and petrochemical industries. Chotest's service network is covered more than 30 provinces in China, and is also focusing on the development in overseas markets like Europe and APAC. The goal of Chotest is to provide high-end dimensional measurement equipment to manufacturing industry all over the world.

From nanometer to hectometer



we provide professional precision measurement solutions

10^{-1}

10^{-0}

10^1

10^2

Hectometer scale

2 μ m

0.5 μ m



CMM



Machine Tool Probes



Laser Interferometer



Wireless Ballbar



3D Line-Scanning
Profilometer



Microscopic
Measuring Machine



Rotary Axis Calibrator



Laser Tracker



Flash Measuring Machine



Unpatterned Wafer
3D Inspection System



High-Precision
Laser Rangefinder

Measurement Solutions for Full-Scale Chain

We are committed to providing full-scale chain solutions for different customers and different industries. With our expertise, technologies, various instruments and software, we can reduce costs and increase efficiency for our customers, at the same time, continuously improve product quality, which helps customers to enhance their market competitiveness.





Aviation/Aerospace/Shipbuilding Industry Application



Automotive/New Energy Industry Application



3C Electronics Industry Application



Semiconductor Industry Application



Aviation/Aerospace/Shipbuilding Industry Application

As an important part of the equipment manufacturing industry, the aerospace and Shipbuilding industry is an important field for implementing the innovation-driven development strategy and an important support for building a manufacturing power. Chotest provides a full range of dimension measurement solutions in the industrial chain system including the whole machine manufacturing, power system, key components, key basic materials, etc



As an important part of the equipment manufacturing industry, the aerospace and Shipbuilding industry is an important field for implementing the innovation-driven development strategy and an important support for building a manufacturing power. Chotest provides a full range of dimension measurement solutions in the industrial chain system including the whole machine manufacturing, power system, key components, key basic materials, etc.

P109



For parts such as aero-engines and gear blades, Chotest Coordinate Measuring Machines Mars series can provide high-efficient and precise dimensional inspection

CMM,coming



With the high measurement accuracy and large measurement range, Chotest GTS laser tracker is used in various assembly application scenarios such as airplane & rocket & vessel assembly and profile measurement.

P91





Chotest Video Measuring Machines/Flash Measuring Machines support non-contact fast and magnified measurement. The software Vision X has more than 90 measurement functions, and has special measurement tools for sealing rings, springs, gears, threads and other workpieces. It can perform simple, fast and accurate measurement, and it is the best measurement method for small parts or small-size features, thin-walled parts, and soft parts.

P21/P33




Chotest high-precision Profilometer SJ5730, with 2 in 1 (roughness and profile) measurement module, is often used to measure the surface profile shape and roughness of the engine fuel nozzles and engine crankshaft connecting rods.

P115



Chotest universal length measuring machine SJ5100 is often used to calibrate measuring gauges in aerospace metrology labs and to measure the ultra-high-precision piston rods, which is one of the core components of aero- engines.

P141



Automotive/New Energy Industry Application

The automotive and new energy industries are witnessing rapid growth, driven by the rapid expansion of new energy vehicles. Chotest provides solutions for various dimension measurements in the entire production process, from battery production stages, modules, battery packs, electric motor components, electronic control modules, to complete vehicle bodies.

Automotive Research Institute



Chotest Universal Thread Measuring Machines can calibrate the full parameters of the thread, helping the precision manufacturing of automobiles.

P145



Chotest universal length measuring machine SJ5100 is used to calibrate the gauges and other measuring tools, which are widely used in major automobile research institutes.

P141



Chotest fully automatic dial indicator testing machines SJ2000 Series can automatically calibrate various plunger dial indicators, digital dial indicators, dial test gauges, dial bore gauges, mechanical comparators, etc.

P149

Bodywork



Chotest Coordinate measuring machines Mars series support high precision and high speed measurement for car body.

CMM,coming



Chotest Laser tracker is a flexible and large-range measurement method for the car body, and has been recognized and accepted by the automobile OEM and their supporting factories. As a supplement to the Chotest Coordinate Measuring machine, Chotest Laser Tracker is appearing more and more in the workshops of automobile OEM.

P91



Chotest Coordinate measuring machine Mars series is used in the design and trial production of new models.

CMM,coming



Chotest Video Measuring Machines can measure the sizes of various auto parts.

P21



Chotest 2D profilometers SJ5700 series can inspect the tiny dimensions of auto parts, and ensure the high processing accuracy of parts.

P109

Powertrain



Chotest Coordinate Measuring machine is crucial to ensuring the quality and performance of the powertrain and even the entire vehicle.

CMM,coming



Chotest 2D profilometers SJ5700 series can measure the tiny dimensions of automobile engines, gearboxes and other parts.

P109



Chotest Video Measuring Machines / Flash Measuring Machines can quickly and accurately measure the XY sizes of small auto parts.

P21/P33

Automotive parts



Chotest Coordinate Measuring machine is an ideal solution for geometric measurement and quality control of cylinder parts.

CMM,coming



Chotest 2D profilometers SJ5700 series can measure the tiny dimensions of automobile cylinder head parts.

P109



Chotest Video Measuring Machines/ Flash Measuring Machines can efficiently measure the diameter and center distance of the connecting rod.

P21/P33



Chotest horizontal Flash Measuring Machine VX5000 series can easily measure the size of shaft parts, making the measurement process simple, efficient and accurate.

P71



Chotest Nano 3D Optical Surface Profilometers can measure the surface profile of the fuel injector at the sub-nanometer level.

P75



Chotest 2D profilometers SJ5700 series can measure both roughness and profile of the workpieces.

P109



Chotest Machine tool probes PO series can control the machining process of auto parts, and realize large-scale on-line measurement of parts after machining, ensure machining accuracy.

P127



Chotest Laser interferometer SJ6000 can calibrate and compensate CNC machine tools for the position accuracy (positioning accuracy repeatability, positioning accuracy, etc.) and geometric accuracy (pitch and yaw angle, straightness, verticality, etc.).

P97

Camera/LIDAR



Chotest Laser interferometer SJ6000 can calibrate and compensate CNC machine tools for the position accuracy (positioning accuracy repeatability, positioning accuracy, etc.) and geometric accuracy (pitch and yaw angle, straightness, squareness, etc.).

P97

Chotest Nano 3D Optical Surface Profilometers can measure the surface flatness & roughness and 3D shape of the radar chip.

P75

Power Battery



Chotest Coordinate Measuring machine achieves precision measurement of length & width, flatness, assembly hole position and step height of battery pack.


CMM,coming



Chotest Flash Measuring Machines/ Video Measuring Machines provide a precision and stable measurement solution for top covers of power battery.

P21/P33





3C Electronics Industry Application

Chotest provides a series of measurement equipment to control the product processing quality in the 3C industry. The software presents datafication results, which can be used to improve design and re-producing.

The adjoint geometric measurement system solves the geometric measurement problems in the whole production process, and realizes the systematic and efficient process control and quality management



Chotest Flash Measuring Machines/ Video Measuring Machines can realise high-precision measurements of different sizes and varying structures by one click .

P21/P33



Chotest Machine tool probes PO series are 100% tested by self-developed inspection equipment to ensure quality and stability; Completely replaceable with international famous probes. Laser interferometer SJ6000 and Rotary axis calibrator WR50 are used to calibrate the guide rail of CNC machine tools. Moreover, Chotest Wireless ballbar MT21 can diagnose CNC machine tools' performance quickly.

P127



Measurement head + automation module + customized 2D and 3D automatic dimensional measurement functions constitute a efficient measurement solution for some special & difficult scenarios.

P131



Chotest Nano 3D Optical Surface Profilometers can measure the roughness, flatness and step height of sapphire screens, phone glass screens, ink screens, etc.

P75




Chotest 2D profilometers SJ5730 series, with micro measuring force and high precision performance, is suitable for fast measurement of easy-to-scratch surfaces, such as the thickness of screen-printing ink on the front cover of mobile phones.

P109




In the 3C field, Chotest coordinate measuring machine is not only used in inspection of the plane sizes and GD & T, but also used in measurement of the curved surfaces, mobile phone screen corners, chamfers, etc.


CMM,coming



Semiconductor Industry Application

In recent years, with higher and higher requirements to product quality in the chip manufacturing industry, more sophisticated measurement instruments are required to ensure product quality. Integrating self-developed software algorithms, Chotest precision measurement equipment perfectly caters for this kind of demands.





Chotest Nano 3D Optical Surface Profilometer is a non-contact scanning method to achieve 3D re-construction of the sample surface with ultra-high repeatability&accuracy, and obtains relative 2D and 3D measurement data.

P75




Unpatterned Wafer 3D Inspection System WD4000 adopts white light confocal probes and white light interferometry probe to scan and reconstruct 3D surface topography of the wafer, then obtains the relative 2D and 3D parameters of thickness, BOW, WARP, flatness, line roughness, and Total Thickness Variation (TTV).

P131




Patterned Wafer Critical Dimension & Overlay Measurement System can not only inspect the critical dimensions of wafer and the offset of overlay, but also measure the 3D surface form and roughness of wafer at the sub-nanometer level. Automatic robot arm can load and upload the test objects aumatically, which helps to achieve fully automated production in the workshop.

P135



Chotest Confocal microscope VT6000 series can reconstruct surface 3D topography by non-contact scanning, and has better imaging effects on surface with large slopes. It is be widely used in semiconductor manufacturing and packaging process inspection.

P85



Chotest Video Measuring Machines/- Flash Measuring Machines are mainly used in semiconductor packaging process, and they measure the substrates, lead frames, ceramic parts efficiently by one-click.

P21/P33



Chotest Stylus Nano Profiler CP200 can measure the film thickness & step height, surface topography and surface waviness & roughness by contact scanning. Thanks to micro measuring force, CP200 absolutely does not scratch the surface of test object at all.

P125



Optical Measurement Instruments

P19

Video Measuring Machines CHT Series	P21	Confocal Microscope VT6000 Series	P85
Video Measuring Machines Novator Series	P29	Microscopic Measuring Machine MX3200	P89
Flash Measuring Machines VX Series	P33	Laser Tracker GTS3000 Series	P91
Flash Measuring Machines Hybrid Series	P73	Laser Tracker GTS6000 Series	P96
3D Optical Surface Profilometer SuperView W1	P75	Laser interferometer SJ6000	P97
3D Optical Surface Profilometer SuperView W3	P79	Rotary Axis Calibrator WR50	P101
3D Optical Surface Profilometer SuperView W5	P81	Wireless Ballbar MT21	P105
White Light Interferometry Probe SuperView WX100	P83		

Contact Measurement Instruments

P107

Intelligent Profilometer SJ5780 Series	P109	Economic Profilometers SJ5718 Series	P123
Profilometers for Optics Surface SJ5720-OPT Series	P111	Stylus Nano Profiler CP200	P125
Profilometers SJ5730 Series	P115	Machine Tool Probes PO Series	P127
Profilometers SJ5760 Series	P119		

Professional Inspection Equipment

P129

Unpatterned Wafer 3D Inspection System WD4000	P131	Patterned Wafer Critical Dimension & Overlay Measurement System BOKI_1000	P135
---	------	---	------

Dimensional Calibrators

P139

Universal Length Measuring Machines SJ5100 Series	P141	Automated Dial Indicator Testing Machines SJ2000 Series	P149
Universal Thread Measuring Machines SJ5200 Series	P147		
Universal Thread Measuring Machines SJ5500 Series	P148		




Optical Measuring Instrument



Automatic Video Measuring Machines CHT Series

Precision, Versatile



Bridge-Type

Column-Type

Description

Automatic video measuring machines CHT series covers different measurement ranges and offers powerful functionality. It can perform precise measurements of surface dimensions, contours, angles, positions, and geometric tolerances for various complex parts.

Automatic video measuring machines CHT series can be used in machinery, electronics, mold, injection molding, hardware, rubber, low-voltage electrical appliances, magnetic materials, precision stamping, connection Plug-ins, connectors, terminals, mobile phones, home appliances, printed circuit boards, medical equipment, clocks, knives, measurement and testing, etc.

Automatic Report Generation



Automatically output SPC analysis report and support remote data docking

Measurement Function

		Extraction Tools	Scanning to extract edge points, multi-segment edge point extraction, circular edge point extraction, ellipse extraction, frame selection to extract contour lines, focus points, closest points, etc.
		Annotation Tools	Point, line, circle (center coordinates, radius, diameter), arc, center, angle, distance, line width, hole position, aperture, number of holes, distance from hole to hole, distance from hole to edge, distance from arc center to hole, the distance from the center of the arc to the side, the distance from the high point of the arc to the high point of the arc, and the distance from the intersection to the intersection, etc.
		Construction	Intersection point, center point, extreme point, end point, line connecting two points, parallel line, perpendicular line, tangent line, bisector, Centerlines, line segment fusion, radius circle, three-line inscribed circle, two-line radius inscribed circle, etc.
		GD&T	Straightness, roundness, profile, position, parallelism, symmetry, perpendicularity, concentricity and other form and position tolerance evaluation
		Coordinate	Instrument coordinate system, point to line, point to point, line to line and other workpiece coordinate systems; image registration coordinate system; Can translate, rotate, manually adjust the coordinate system
		Special Tools	R angle, horizontal pitch, circumferential pitch, screen, slot, contour comparison, spring, O-ring and other special tools for rapid measurement.
			Support tolerance batch setting, scale classification, and color custom management


Easy to operate

With user-friendly software,
anyone can be trained to use it quickly



Programming

Save program



Place objects

Place test objects
on object table




Batch meas.


Measure all features
by one-click

Flexible shooting and precise calculation

Support segmental programming control of surface light, transmitted light and coaxial light ,
automatically identify the measurement position, and obtain uniform and stable measurement results
every time.




Ring light



Surface features are clear




Back light



Easy to measure profile features



Coaxial light




Measure diameter of blind hole

Auto batch measurement

- The program matches the coordinate system of the workpiece, automatically executes the measurement process, supports the import of CAD drawings and Gerber drawings, and coordinates system matching measurement;
- In the CNC fixed coordinate system mode, batch measurement can be performed quickly and accurately.



Import CAD drawing to build a program



CNC batch measurement

Various accessories


- Equips a touch probe or optical probe to measure height and flatness and realize 2.5D space measurement;
- Supports external input from digital calipers and height gauges; Supports label printers.



Height measurement



Flatness measurement



Height result



Flatness result

Parameters

Model No.		CHT322A	CHT432A
Travel Range	X	300 mm	400 mm
	Y	200 mm	300 mm
	Z	200 mm	200 mm
Structure Type		Column	
Base Material		Marble	
Monitor		24" LCD(1920×1080)	
Image Sensor		160w High definition colorful industrial camera	
Resolution of Glass scale		0.5μm	
Lens		6.5X manual lens	
Magnification		Optical Zoom: 0.7X~4.5X, Image Zoom: 32~206X	
Light	Back light	Telecentric transmission illumination	
	Ring Light	5 rings and 8 segments (256 levels) surface light	
Accuracy*1	X/Y	(2.5+L/200)μm	
	X⊥Y	(3.0+L/200)μm	
	Z*2	(5.0+L/200)μm	
Max Speed	XY	500 mm/s	
	Z	100 mm/s	
Size		760×1220×1670 mm	860×1350×1670 mm
Weight		600 kg	650 kg
Loading Capacity		25 kg	
Power		1500W	2000W
Sensor Option		(1)Touch probe; (2)Laser probe	
Motion Control		Servo control system	
Software		InsightX	
Input		AC200~240V, 50/60Hz	
Working Environment		Temp.20°C ±2°C, Humidity 20~80%, Vibration<0.002g, Less than 15Hz	

Note:

*1 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 5 kg or less;

L is the moving range of the table in mm.

*2 It is mechanical accuracy, and actual accuracy depends on object surface where lens focuses.

Parameters

Model No.		CHT322U	CHT432U
Travel Range	X	300 mm	400 mm
	Y	200 mm	300 mm
	Z	200 mm	200 mm
Structure Type		Column	
Base Material		Marble	
Monitor		24" LCD(1920×1080)	
Image Sensor		160w High definition colorful industrial camera	
Resolution of Glass scale		0.1μm	
Lens		8.3Xmotorized lens	
Magnification		Optical Zoom: 0.6~5.0X, Image Zoom: 27~229X	
Light	Back light	Telecentric transmission illumination	
	Ring Light	6 rings and 8 segments (256 levels) surface light	
	Coaxial Light	LED	
Accuracy*1	X/Y	$(2.0+L/200)\mu\text{m}$	
	$X\perp Y$	$(3.0+L/200)\mu\text{m}$	
	Z*2	$(4.5+L/200)\mu\text{m}$	
Max Speed	XY	500 mm/s	
	Z	100 mm/s	
Size		760×1220×1670 mm	860×1350×1670 mm
Weight		600 kg	650 kg
Loading Capacity		25 kg	
Power		1500W	2000W
Sensor Option		(1)Touch probe; (2)Laser probe	
Motion Control		Servo control system	
Software		InsightX	
Input		AC200~240V, 50/60Hz	
Working Environment		Temp.20°C ±2°C, Humidity 20~80%, Vibration<0.002g, Less than 15Hz	

Note:

*1 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 5 kg or less;

L is the moving range of the table in mm.

*2 It is mechanical accuracy, and actual accuracy depends on object surface where lens focuses.

Parameters

Model No.		CHT452	CHT562	CHT682
Travel Range	X	400 mm	500 mm	600 mm
	Y	500 mm	600 mm	800 mm
	Z	200 mm	200 mm	200 mm
Structure Type		Bridge		
Base Material		Marble		
Monitor		24" LCD(1920×1080)		
Image Sensor		160w High definition colorful industrial camera		
Resolution of Glass scale		0.1μm		
Lens		8.3Xmotorized lens		
Magnification		Optical Zoom: 0.6~5.0X, Image Zoom: 27~229X		
Light	Back light	Telecentric transmission illumination		
	Ring Light	6 rings and 8 segments (256 levels) surface light		
	Coaxial Light	LED		
Accuracy*1	X/Y	(2.5+L/200)μm		
	X⊥Y	(3.0+L/200)μm		
	Z*2	(4.5+L/200)μm		
Max Speed	XY	500 mm/s		
	Z	100 mm/s		
Size		950×1320×1700 mm	1100×1600×1700 mm	1200×2000×1700 mm
Weight		1400 kg	1500 kg	2000 kg
Loading Capacity		25 kg		
Power		2000W	2500W	2500W
Sensor Option		(1)Touch probe; (2)Laser probe		
Motion Control		Servo control system		
Software		InsightX		
Input		AC200~240V, 50/60Hz		
Working Environment		Temp.20°C ±2°C, Humidity 20~80%, Vibration<0.002g, Less than 15Hz		

Note:

*1 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 5 kg or less;

L is the moving range of the table in mm.

*2 It is mechanical accuracy, and actual accuracy depends on object surface where lens focuses.

Parameters

Model No.		CHT0810	CHT1012	CHT1215
Travel Range	X	800 mm	1000 mm	1200mm
	Y	1000 mm	1200 mm	1500mm
	Z	200 mm	200 mm	200 mm
Structure Type		Bridge		
Base Material		Marble		
Monitor		24" LCD(1920×1080)		
Image Sensor		160w High definition colorful industrial camera		
Resolution of Glass scale		0.1μm		
Lens		8.3Xmotorized lens		
Magnification		Optical Zoom: 0.6~5.0X, Image Zoom: 27~229X		
Light	Back light	Telecentric transmission illumination		
	Ring Light	6 rings and 8 segments (256 levels) surface light		
	Coaxial Light	LED		
Accuracy*1	X/Y	(3.0+L/200)μm	(3.5+L/200)μm	
	X⊥Y	(4.0+L/200)μm	(4.5+L/200)μm	
	Z*2	(4.5+L/200)μm	(4.5+L/200)μm	
Max Speed	XY	500 mm/s		
	Z	100 mm/s		
Size		1750×2220×1700	2150×2620×1700	2550×3220×1700
Weight		2900 kg	3600 kg	4500kg
Loading Capacity		50kg		
Power		2500W	2500W	2500W
Sensor Option		(1)Touch probe； (2)Laser probe		
Motion Control		Servo control system		
Software		InsightX		
Input		AC200-240V, 50/60Hz		
Working Environment		Temp.20℃ ±2℃ , Humidity 20~80%, Vibration<0.002g,Less than15Hz		

Note:

*1 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 5 kg or less;

L is the moving range of the table in mm.

*2 It is mechanical accuracy, and actual accuracy depends on object surface where lens focuses.

Automatic Video Measuring Machines

Novator Series




Functions

1. Measurement tools: Extracting edge points by scanning, extracting edge points by multi-segment, extracting edge points by circle, ellipse extraction, extracting contour line by frame selection, focus point, nearest points, etc.
2. Measure geometric features: Point, line, circle (center coordinate, radius, diameter), arc, center, angle, distance, line width, hole site, aperture, number of holes, distance from hole to hole, hole to edge, distance from the arc center to the hole, distance from the arc center to the edge, distance from the arc high point to the other arc high point, distance from the intersection to the intersection, etc.
3. Construction features: Intersection, center point, extreme point, endpoint, two-point connection, parallel line, perpendicular line, tangent, bisector, center line, line segment fusion, drawing circle by radius, drawing inscribed circle among three lines, drawing inscribed circle by two lines & radius , etc.
4. Geometric tolerance: Straightness, roundness, contour, position, parallelism, symmetry, perpendicularity, concentricity, and other shape and position tolerance evaluation.

Features



Replaceable RGB surface light



Integrate 3D topography measurement

■ Stable moving stage, high measurement accuracy

1. Precision marble body, good stability and high precision.
2. Precision linear slide rail and servo control system, smooth and silent movement.
3. Three axes x/y/z programmable, realize batch inspection for complex features.

■ Laser scanning imaging, 3D composite measurement

1. Support spot-type laser probe to scan profile in height direction.
2. Support 3D line-scanning laser probe.
3. VisionX supports a variety of contour measurements and 3D spatial measurements, seamlessly connecting 2D/3D hybrid measurements.

■ Strobe lighting source, high speed fly-shooting

1. Equipped with strobe lighting source, support strobe and normal lighting modes.
2. Support fly-shooting measurement mode, measurement efficiency is increased by 5~10 times.
3. Support the stitching measurement function of the flash measuring machines.

■ Replaceable RGB surface light, independent lifting up and down

1. RGB and white light can be replaced to adapt to a variety of complex colors and material surfaces.
2. The surface light can be lifted independently to better observe the sample surface.
3. Support programmable back light, coaxial light and 6 rings and 8 segments of the surface light.


■ Automatic and fast batch measurement

1. The program matches the workpiece coordinate system and automatically executes the measurement process.
2. Support CAD drawing and Gerber drawing import.
3. Can execute quickly and accurate batch measurement in CNC fixed coordinate system mode.

■ Easy operation, hassle-free

1. Equipped with a large FOV navigation camera for fast workpiece positioning.
2. Mechanical lens anti-collision function
3. User-friendly operation interface, anyone can easily set and measure.

Software Interface



User-Friendly Operation Interface

Auto data export

- Output SPC analysis report, which includes statistical values (such as CA, PPK, CPK, PP, etc.) and control charts (such as mean and range charts, mean and standard deviation charts, median and range charts, single value and moving range chart).
- Can output Excel, Word, PDF, TXT reports and AutoCAD files.
- Support exporting data to designated excel file according to designated template in real time
- Support Q-DAS transmission according to designated format.
- Support data exchanging via HTTP or socket protocol

Parameters

Model No.		Novator333	Novator432	Novator562	Novator682
Travel Range	X	300 mm	400 mm	500 mm	600 mm
	Y	300 mm	300 mm	600 mm	800 mm
	Z	300 mm	200 mm	200 mm	200 mm
Structure Type		Bridge	Bridge	Bridge	Bridge
Base Material		Marble	Marble	Marble	Marble
Monitor		24" LCD(1920×1080)			
Image Sensor		5M High definition colorful industrial camera			
Resolution of Glass scale		0.1μm			
Lens		13.3X motorized lens			
Magnification		Optical Zoom: 0.6X~8.0X, Image Zoom: 17X~380X			
F.O.V.		Max: 13x11mm; Min:1.0x0.8mm			
Light	Back light	Telecentric transmission illumination			
	Ring light	6 rings and 8 segments (255 levels) surface light(or RGB surface light,Optional)			
	Coaxial Light	LED			
Accuracy*1	X/Y	(1.6+L/250)μm	(1.6+L/250)μm	(1.8+L/250)μm	(2.0+L/250)μm
	X⊥Y	(2.0+L/250)μm	(2.0+L/250)μm	(2.2+L/200)μm	(2.5+L/200)μm
	Z	(3.0+L/200)μm	(3.0+L/200)μm	(3.0+L/200)μm	(3.0+L/200)μm
3D Scanning*2	Z measuring range*3	5mm			
	Scanning width*4	30mm			
	Repeatability*5	±1μm			
	Z Accuracy*5	±0.1%F.S.			
	Scanning speed	10~80mm/s			
Fly-Shooting Mode		Support			
Navigation camera		Support			
Sensor Options		(1)Touch probe; (2)Laser probe			
Max Speed	XY	500 mm/s			
	Z	100 mm/s			
Size		900×1380×1700mm	1000×1380×1700mm	1100×1820×1700mm	1200×2030×1700mm
Weight		800kg	1200kg	1650kg	2000kg
Loading Capacity		25kg	25kg	50kg	50kg
Power		2000W	2000W	2500W	2500W
Motion Control		Servo control system			
Software		InsightX			
Input		AC200~240V, 50/60Hz			
Working Environment		Temp.20℃ ±2℃ , Humidity 20~80%, Vibration<0.002g, Less than15Hz			

*1 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 5 kg or less;

L is the moving range of the table (mm)

*2 Optional line-scanning probe is required.

*3 Measuring range 5mm~40mm optional.

*4 Scanning width 30mm~145mm optional.

*5 Environment temperature is +20 °C ± 1.0 °C

Flash Measuring Machines VX Series

One Touch Measurement
Efficient Accurate



VX8000 series



VX3200D / VX3300D series



VX3100D / VX3030D series



VX1000 series



VX3500 / VX8500



VX4000 series



VX5000 series

■ Solve the problems of traditional measuring instruments

Traditional measuring instruments, such as projectors, video measuring machines, tool microscopes, profilometers, vernier calipers, micrometers, etc., face many problems when measuring, such as: time-consuming for positioning of measurement objects and origin positioning, long operation time for batch measurement, different results from different operators for the same sample, and the complicated data statistical management.

Traditional measuring instruments	VX Series
<p> Measurement speed is slow</p> <ul style="list-style-type: none"> ■ Test object needs to be positioned, and it is time-consuming. ■ The more features or parts, the longer time. ■ Long time operation makes worker very tired. 	<p> Fast and efficient</p> <ul style="list-style-type: none"> ■ Products can be placed at will ■ Measure up to 5000+ features once ■ Fast and accurate batch measurements
<p> The results are discrepant</p> <ul style="list-style-type: none"> ■ Different operation methods lead to different results. ■ Different focusing methods lead to different results ■ Different extraction positions lead to different results 	<p> Accurate and consistent</p> <ul style="list-style-type: none"> ■ Just one touch, anyone can easily get accurate and consistent results ■ AutoFocus, no deviation caused by focus adjusting ■ Auto identify test location Always get uniform and stable results
<p> Difficult to operate</p> <ul style="list-style-type: none"> ■ It takes long time to learn operation ■ Unskilled people cannot measure correctly ■ Measurement of virtual lines and virtual points requires professional knowledge 	<p> Simple and easy</p> <ul style="list-style-type: none"> ■ Anyone can be trained to use it quickly ■ User-friendly software allows anyone to measure easily and correctly ■ Measurement of virtual lines and virtual points can also be easily set

Efficient measurement

5000+ pcs

Once up to
5000+features

1024 pcs


Once up to
1024 workpieces

2 secs

In 2 seconds
Finish the
measurement

- Auto illumination
- Auto focusing





Dedicated Optical Lens




Normal Lens




Our Dedicated lens

Clear image even if there are stages

Equipped with a high depth optical lens and automatic focusing, the flash measuring machine only needs to focus at the tested object once. Even if there are variations in height, the images remain clear.




Normal Lens




Our Dedicated lens

Always real size even if there are stages

With a double telecentric optical lens, the size of objects in the image is always real and accurate, even features that are located at edge of the field of view.




Normal Lens




Our Dedicated lens

Zero distortion in the full field of view

Thanks to the double telecentric optical lens with high depth of field and high resolution, it is almost zero distortion of the image in the full field of view. Test result is always the same in any position of the object table.



Normal Lens



Our Dedicated lens

Sub-pixel processing of edges


With algorithms of high-order interpolation and numerical fitting, the software can perform sub-pixel processing of the edges.

Light Source


Back light





Coaxial light




75°Ring light



0° ring light




Height probe



It is a white light confocal probe, and can be used to measure thickness, height difference, flatness, parallelism, etc. Moreover, this probe can scan the surface of the sample continuously.


Rotary chuck



Rotary chuck can rotate 360°. It is convenient to measure the sizes in different section according to rotation angle specified by the operator. It is an ideal solution to measure all kinds of cylindrical parts, such as shaft, etc.

Software

VisionX professional visual measurement software is completely independently developed by CHOTEST, and CHOTEST has independent intellectual property rights. VisionX has friendly user interface, convenient operation, powerful and practical functions, support more than 80 kinds of extraction and analysis tools, including feature extraction tool, auxiliary tool, annotation tool and special application tool, etc. Moreover, functions can be customized according to user's need, so as to improve work efficiency more effectively.



Home Interface


Features

Geometric Tolerance	Straightness, Roundness, Concentricity, Symmetry, Positional Tolerance, Parallelism, Perpendicularity, Profile Tolerance, etc.
CNC Mode	Modify CNC program anytime, as well as adding or reducing features OK or NG is concluded according to tolerance in CNC program
Automatic	Only need to select the measuring features, after placing the workpiece, measuring results can be obtained quickly by one key
Coordinate System	Can create coordinate system by Point-line, Line-line, and translate & rotate coordinate system, as well as create multi-coordinate system
Special tools	Rounded corner, Contour, Thread, Slot, Perimeter, Pitch distance, Thickness, Chamfer, Spring, Gear, Sealing gasket, area, Pitch Angle, Boundary width




DXF Import


Measurement data can be obtained from CAD drawings. Even if the test object is not physically available, you can still create measurement programs quickly. The system can automatically assign features and dimensions from the DXF drawing to the sample, including surface dimensions



Sample




Automatically assign DXF features to the sample




CNC Measure

Profile Degree

- This tool has three evaluation methods: No reference (only shape error evaluation), Single reference, Multiple references.




- Multiple annotations: Multiple profile degrees can be annotated in a single program. No need to establish a coordinate system: Just need to enter the reference in the drawing. Measurement of profile degrees in different coordinate systems can be achieved in a single program.
- Multiple types: Evaluate the profile degree by scanning the entire contour; Or evaluate the profile degree by measuring point with specifying coordinate values.




Position Degree

It can measure both point position degree and line position degree. Evaluation can be performed by XY coordinates in Cartesian coordinate system or radius & angle in polar coordinate system.




QR Code Recognition

The QR code on the sample can be defined as inspection information.




The QR value which is recognized by the software can be saved as inspection information according to pre-setting during CNC measurement.




Automatic Multi-Object Matching

The system supports automatic measurement of multiple objects, up to 1024 objects at a time. 360-degree rotation search function, tested objects can be easily recognized and automatically measured, regardless of their orientation. The measurement sequence of the samples can be customized.



Z-order numbering



N-order numbering

Extract Multi-Circle by Lasso

When there are many circles located together on a sample, extracting circles one by one can be time-consuming and labor-intensive. This tool allows the diameter of the circles to be quickly extracted and annotated all at the same time.




Select area by lasso



Exact all circles automatically



Fixed Position Measurement

Fixed position measurement eliminates the matching process, and the tested objects need to be placed in the same position. During CNC measurement, only images of the measurement areas are captured, greatly enhancing measurement efficiency. Even for samples with significant deformation, such as rubber seals, automatic CNC measurement can be achieved through fixed position measurement.



Seal Measurement

Accurate measurements can be performed even for seal rings with large deformations.




Conjoint program

Combine Wide F.O.V. and High Precision F.O.V. : Wide F.O.V. mode allows efficient measurement for large dimensions. High precision F.O.V. mode focuses on small dimensions of the test object, ensuring accuracy.




Software can combine two programs with different measurement views of the test object as a Conjoint one. During CNC measurement, two sub-programs can be performed sequentially on different views, then all data can be generated to a single measurement record for easy data management and statistic.



The barcode value which is read by Scanner can be saved as inspection information, or used to search program according to definition of the operator.



The accounts can be defined as administrator or operator, and user rights of the operator account could be constrained according to requirement.



Statistical Analysis

The statistical analysis interface has the tabs of [Statistical Value], [Trend Chart], [Histogram] and [Data List]


■ Automatic recording and sorting

Measurement results and its main statistical information (e.g. average value, σ , 3σ , 6σ , Ca, Cp, Cpk etc) will be automatically recorded and saved. Operator could search records by different conditions.





Statistic




Tabled data


■ Control production process and improve product quality

The trend chart monitors the abnormalities of generating equipment and production process by regularly changing trend of measured values. Such as the monotonic and periodic changes of the measured values.

The histogram reflects the fluctuation and distribution of product quality, and transmits information about process quality, which can be used to judge and predict product quality and unqualified rate.




Trend Chart



Histogram

By quality diagnosis and analysis, SPC statistical method can not only realize the monitoring of product quality, but also reflect the change trend in the generation process, reduce the waste caused by post-inspection, so as to achieve the effect of controlling the production process and improving product quality.



Control Charts

■ Generate measurement report automatically by One Key

1. Import and export Measurement records
2. Able to saved as PDF, CSV, Excel ,text files
3. Support user-defined PDF report template
4. Support user-defined Excel report template
5. Quick export and print reports by one key

Test Report							
				Date:	2020-08-20 15:00:00		
				Project:	3M Cast Tray 45		
				Model:	3M-45		
				Operator:	M		
				Quantity:	1		
				Temp:	25		
No.	Feature	Unit	Measured Value	Nominal	Upper Dev.	Lower Dev.	Judge
1	h	mm	8.146	8.170	0.030	-0.020	NG
2	11-1	mm	14.818	14.800	0.010	-0.050	OK
3	11-2	mm	14.832	14.800	0.030	-0.050	OK
4	12-1	mm	15.079	15.100	0.020	-0.070	OK
5	12-2	mm	15.119	15.100	0.010	-0.070	OK
6	13	mm	35.840	35.840	0.000	-0.070	OK
7	15	mm	25.877	25.900	0.020	-0.060	NG
8	14-1	mm	26.842	26.800	0.040	-0.080	NG

Test report

Evaluation Methods


Standard Tolerance

Evaluate the measured values against the given design value and upper/lower tolerances specified on the drawing.

ID	Feature name	Measured value	Assessment result	Design value	Upper dev.	Lower dev.
1	Two lines(D1)	14.0731	OK	14.0700	0.0500	-0.0500
2	Dia(D1)	16.0572	OK	16.0500	0.0500	-0.0500
3	Point position (X1)	0.1689	OK	0.2000	0.0500	-0.0500
4	Point position (Y1)	9.5407	OK	9.5500	0.1000	-0.1000
5	Positional alignm.	0.0066	OK		0.1000	
6	Concentricity(φ1)	0.0064	OK		0.1000	
7	Dia(D2)	17.9646	OK	17.9600	0.0500	-0.0500
8	Concentricity(φ2)	16.7549	OK	16.8000	0.0500	-0.0500

Grade of Tolerance

Divide the tolerance into multiple grades according to deviation range. Evaluate the sample's grade based on the actual measured value; If the dimensions of a sample are not in the same grade, this sample is unqualified. Classifying samples into different grades facilitates assembly and reduces waste.



■ Proportion of Tolerance

Divide the tolerance into multiple grades according to tolerance percentage. Evaluate the sample's grade based on the actual measured value, so it can be used for pre-warning of processing equipment's state.

ID	Feature name	Measured value	Assessment result	Belong to range	Design value	Upper dev.
5-1	Radius(R1)	14.0624	G1	(0.00%, 80.00%)	14.0700	0.0250
5-2	Dia(JD1)	16.0798	G1	(0.00%, 80.00%)	16.0500	0.0250
5-3	Point position-XP(1)	0.2293	G2	(80.00%, 100.00%)	0.2000	0.0250
5-4	Point position-YP(1)	-9.5128	G1	(0.00%, 80.00%)	9.5500	0.1000
5-5	Positional alignm.	0.0846	G2	(80.00%, 100.00%)		0.1000
5-6	Concentricity(φ1)	0.0093	G1	(0.00%, 80.00%)		0.1000
5-7	Dia(JD2)	17.5727	G1	(0.00%, 80.00%)	17.9600	0.0250
5-8	Vertical(r1)	19.7822	G1	(0.00%, 80.00%)	19.8000	0.0250

■ Critical Dimensions

The sample is qualified by only Critical Dimensions which are specified by the operator.



■ Data

Test reports can be generated simple and fast, such as PDF, WORD, EXCEL, CSV and TXT.

■ Process Statistics:

Automatically calculate Cp and Cpk. Real-time trend chart or histogram display quality trends and changes during measurements.

■ Custom Excel Report

Measurement data & corresponding test images and inspection info are automatically exported into a designated Excel template in real time.

Customer		LOT No	
Part name		Material	
Part No.		Spec.	

Batch No.	Item	Measured value	Design Value	Upper Limit	Lower Limit	Inspector	Date
D8X62723-E75-P-N-1	L①	2.513	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L②	2.512	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L③	2.511	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L④	2.508	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L⑤	2.509	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L⑥	2.511	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L⑦	2.513	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L⑧	2.512	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	L⑨	2.509	2.5	0.2	-0.2	Crane	09.20
D8X62723-E75-P-N-1	W①	1.999	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W②	1.997	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W③	1.998	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W④	1.997	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W⑤	1.997	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W⑥	1.999	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W⑦	1.996	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W⑧	1.999	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	W⑨	1.997	2	0.3	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H①	0.901	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H②	0.904	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H③	0.904	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H④	0.903	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H⑤	0.902	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H⑥	0.905	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H⑦	0.901	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H⑧	0.903	0.9	0.1	-0.1	Crane	09.20
D8X62723-E75-P-N-1	H⑨	0.901	0.9	0.1	-0.1	Crane	09.20

■ TCP


Measurement data is transmitted to the MES system of the customer via socket or HTTP protocols in real time.

VisionX also could receive commands from the external server to load the program and begin measurement, so it is compatible with robotic arms to achieve unmanned measurements.




■ QDAS

Automatically generate test results in a format which can be recognizable by the QDAS system.





K fields can be customized to link VX machines to output parameters.



Custom Text Report: Operator can define the content format of the report in Text file, and the measurement data are exported in real time.


Baseline-Line Distance

There are Three options for Baseline-Line Distance annotation. Select the desired line and annotate it with a single click.




Intelligent Annotating

This tool can annotate distance between two points or two lines, center distance between two circles, max distance or min distance or center distance between line and circle, etc.



Auto Edge Detection


Simply highlight the region where the feature is located, and the system will automatically capture the edge.



Various edge extraction conditions can be set to exclude interference and accurately extract the target feature, even for tiny boundaries.




Extract from dark to bright




Extract from bright to dark

Auto deburring


Automatically remove abnormal points to eliminate the interference of edge burrs, and extract features accurately.



Even if boundary is discontinuous, the system can eliminate interference from nearby features. Complex settings are not required as the system automatically removes abnormal points.




The arcs at both ends of a straight line can also be automatically excluded




Posture Adjustment

The posture adjustment function automatically adjusts the orientation of the lasso to ensure precise feature extraction. Even if the lasso does not contain the target feature appropriately, the system automatically adjusts the posture of the lasso to center on the feature.



Free selection



After auto adjustment

For the measurement of peak point, the operator can set condition to constrain orientation of the lasso to ensure accurate calculation of peak value.




Before posture adjustment




After posture adjustment

Sieve Measurement

Multiple measurements can be made continuously, and the report can be output with the deviation values.




Circles



Squares

Gear/R Gauge Measurement

- Gear parameters can be measured in as fast as 2 seconds, such as pitch distance, tooth spacing, normal line, tooth runout, etc. Splines also can be measure by this tool, and both internal and external gears/splines can be measured.



Gear

- No need to create a program. Place the objects on the table then click Measure.



R Gauge

Application

Flash measuring machines are widely used in industry of machinery, electronics, mold, injection molding, hardware, rubber, low-voltage electrical appliances, magnetic materials, precision stamping, connectors, connectors, terminals, mobile phones, home appliances, printed circuit boards, medical equipment, watches, tools, etc.



Phone case



Phone accessories



Watch inner parts



Watch chain



Machining parts



Stamping parts



Sheet metal parts




Plastic injection parts



Magnetic component



Cutting tools



Small metal parts



Gear



Rubber ring



Spring



Thread, Shaft



Rigid PCB




Soft PCB



Shielding case



Mask board



Ceramic plate



Car monitor frame



Connectors



Battery



Resistors



Filter mesh



Die cutting



Medical drill



Sieve




Radius gauge



Thread template


Foldable Screen of Mobile Phone




Phone Casing



Shielding Covers



Shield slot




Back Cover Glass of Mobile Phone



Plastic



Terminal




Shielding Covers




Medical drill



Die Cutting



Soft PCB



Filter



Parameters

Model No.			VX8200	VX8300
Image Sensor			20M CMOS	
Monitor	Built-in		10.4" LCD(XGA 1024x768)	
	Outside		24"LCD(XGA 1920x1080)	
Acceptance Lens			Double Telecentric Lens	
Light	Ring		Four-segment illumination(White Light/Green light)	
	Bottom		Telecentric transmission illumination(Green Light)	
F.O.V.	Large Field		200x200mm(4 Angles R50)	300x200mm(4 Angles R50)
	High Precision		130x130mm	230x130mm
Resolution			0.1 μm	
Repeatability of Image Meas.	Wide Field	Without Stitching*1	±1μm	
		With Stitching*2	±2μm	
	High Precision	Without Stitching*1	±0.5μm	
		With Stitching*2	±1.5μm	
Accuracy of Image Meas.	Wide Field	Without Stitching*1	±3μm	
		With Stitching*2	±(5+0.02L) μm	
	High Precision	Without Stitching*1	±1.5μm	
		With Stitching*2	±(3+0.02L) μm	
Horizontal Rotary Unit (Optional)	Rotation Angle		Range 360°, Resolution 0.02°	
	Rotation Speed		0.2~2rev/s	
	Max Diameter		Φ 60mm	
Height Meas. (Optical Probe) (Optional)	Measuring Range(X*Y)		_____	120*110mm
	Max Hole/Depth Ratio		_____	1.64
	Dia. of Beam		_____	Φ100μm(Φ18μm optional)
	Resolution		_____	0.25μm
	Z Non-movement	Range(Z)	_____	2μm
		Accuracy	_____	±2μm
	Z Movement	Range(Z)	_____	75mm
Accuracy		_____	±(6+0.01H)μm, H is Z movement height in mm	
XY Object Table	X TravelRange		110mm	210mm
	Y TravelRange		110mm	
	Loading Capacity		7.5kg	
Z-Axis TravelRange			75mm(Motorized)	
Size(LxWxH)			(531x386x731)mm	(531x503x731)mm
Weight			49g	75kg
Input			AC100~240V,50/60Hz, 2A	
Working Environment			Temp.10 °C~35 °C ,Humidity 20~80%, Vibration<0.002g Less than15Hz	

Remark : *1 In the focus position, the environment temperature is +20 °C \pm 1.0 °C

*2 In the focus position, the environment temperature is +20 °C \pm 1.0 °C, and the load on the table is 2 kg or less;
L is the moving range of the table (mm)

Parameters

Model No.			VX3200D	VX3300D
Image Sensor			5M CMOS	
Monitor	Built-in		10.4"LCD(XGA: 1024x768)	
	Outside		24"LCD(XGA: 1920x1080)	
Acceptance Lens			Double Telecentric Lens	
Light	Ring		Four-segment illumination(White Light/Green light)	
	Bottom		Telecentric transmission illumination(Green Light)	
F.O.V.	Large Field		200x200mm	300x200mm
	High Precision		130x130mm	230x130mm
Resolution			0.1μm	
Repeatability of Image Meas.	Wide Field	Without Stitching* ¹	±1μm	
		With Stitching* ²	±2μm	
	High Precision	Without Stitching* ¹	±0.5μm	
		With Stitching* ²	±1.5μm	
Accuracy of Image Meas.	Wide Field	Without Stitching* ¹	±5μm	
		With Stitching* ²	±(7+0.02L)μm	
	High Precision	Without Stitching* ¹	±2μm	
		With Stitching* ²	±(4+0.02L)μm	
Height Meas. (Optical Probe) (Optional)	Measuring Range(X*Y)		_____	120*110mm
	Max Hole/Depth Ratio		_____	1.64
	Dia. of Beam		_____	Φ100μm(Φ18μm optional)
	Resolution		_____	0.25μm
	Z Non-movement	Range(Z)	_____	±2μm
		Accuracy	_____	±2μm
	Z Movement	Range(Z)	_____	75mm
Accuracy		_____	±(6+0.01H)μm, H is Z movement height in mm	
XY Object Table	X TravelRange		110mm	210mm
	Y TravelRange		110mm	110mm
	Loading Capacity		7.5kg	
Z-Axis TravelRange			75mm(Motorized)	
Size(LxWxH)			(531x386x731)mm	(531x503x731)mm
Weight			49kg	75kg
Input			AC100~240V,50/60Hz, 2A	
Working Environment			Temp.10 °C~35 °C, Humidity 20~80%, Vibration<0.002g, Less than 15Hz	

Remark: *1 In the focus position, the environment temperature is +20 °C ± 1.0 °C

*2 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 2 kg or less;

L is the moving range of the table (mm)

Parameters

Model No.			VX3100	VX3030D	VX3100D
Image Senor			5M CMOS		
Monitor	Built-in		10.4"LCD(XGA: 1024x768)		
	Outside		24"LCD(XGA: 1920x1080)		
Acceptance Lens			Double Telecentric Lens		
Light	Ring		Four-segment illumination(White Light/Green light)		
	Bottom		Telecentric transmission illumination(GreenLight)		
F.O.V.	Large Field		W20mmxL130mm	Φ100mmxL200mm	Φ100mmxL200mm
	High Precision		W6mmxL106mm	—————	W20mmxL120mm
Repeatability of Image Meas.	Wide Field	Without Stitching* ¹	±0.5μm	±1μm	±1 μm
		With Stitching* ²	±1 μm	±2μm	±2 μm
	High Precision	Without Stitching* ¹	±0.1μm	—————	±0.5μm
		With Stitching* ²	±0.5μm	—————	±1.5μm
Accuracy of Image Meas.	Wide Field	Without Stitching* ¹	±2 μm	±5μm	±5 μm
		With Stitching* ²	±(4+0.02L) μm	±(7+0.02L) μm	±(7+0.02L) μm
	High Precision	Without Stitching* ¹	±0.7μm	—————	±2μm
		With Stitching* ²	±(2+0.02L) μm	—————	±(4+0.02L) μm
Software			VisionX		
Resolution			0.1μm		
Physical Probe			No		
XY Object Table	X Travelrange		110mm		
	Y Travelrange		—————		
	Loading Capacity		2kg		
Z-Axis Travelrange			35mm(Motorized)		
Size(LxWxH)			(500x280x670)mm	(500x280x670)mm	(500x280x670)mm
Weight			31kg	30kg	31kg
Input			AC100~240V,50/60Hz, 2A		
Working Environment			Temp.10°C~35°C, Humidity 20~80%, Vibration<0.002g, Less than15Hz		

Remark: *1 In the focus position, the environment temperature is +20 °C ± 1.0 °C

*2 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 1 kg or less;

L is the moving range of the table (mm)

Parameters

Model No.		VX1060	VX1100
Image Sensor		20M CMOS	
Monitor		24" LCD (XGA:1920×1080)	
Acceptance Lens		Double Telecentric Lens	
Light	Ring	Four-segment illumination(White Light)	
	Bottom	Telecentric transmission illumination(Green Light)	
F.O.V.		Φ60mm	Φ100mm
Repeatability of Image Meas.		±1μm	±2μm
Accuracy of Image Meas.*1		±3μm	±4μm
Software		VisionX	
Resolution		0.1μm	
Z axis travel range		35mm	
Loading Capacity		3kg	
Size(L×W×H)		500×280×670mm	
Weight		25kg	
Input		AC200~240V , 50/60Hz,10A , 2500W	
Working Environment		Temp.10°C~35°C, Humidity 20~80%, Vibration<0.002g, Less than15Hz	

Remark: *1 In the focus position, the environment temperature is +20 °C ± 1.0 °C

Parameters

Model No.	VX4230S	VX4230
Image Sensor	12M CMOS	
Outside Monitor	24" LCD (XGA:1920×1080)	
Acceptance Lens	Double Telecentric Lens	
Transmission Illumination system	Parallel transmission illumination(White Light)	
Field of view	Φ230mm	200x150mm
Depth of Field	50mm	50mm
Working Distance	400mm	
Repeatability	±2μm	
Accuracy*1	±5μm	
Z axis travel range	65mm	100mm
Software	VisionX	
Resolution	0.1μm	
Loading Capacity	15kg	
Size(L×W×H)	830×605×2030mm	
Weight	375kg	370kg
Input	AC100~240V,50/60Hz, 4A	
Working Environment	Temp.10°C~35°C, Humidity 20~80%, Vibration<0.002g, Less than15Hz	

Remark: *1 In the focus position, the environment temperature is +20 °C ± 1.0 °C

Parameters

Model No.		VX5100
Image Sensor		5M CMOS
Outside Monitor		24" LCD (XGA : 1920×1080)
Acceptance Lens		Double Telecentric Lens
Transmission Illumination system		Telecentric transmission illumination(Green Light)
Field of view		φ100mm
Repeatability		±2μm
Accuracy *1		±5μm
Software		VisionX
Resolution		0.1μm
XY Object Table (Optional)	Rotational Speed	0.2 Revolution/s~2 Revolutions/s
	Diameter	φ60mm
	Capacity	3kg
Size(L×W×H)		(736×200×325)mm
Weight		25kg
Input		AC100~240V,50/60Hz,1.3A
Working Environment		Temp.10 °C~35 °C, Humidity 20~80%, Vibration<0.002g, Less than15Hz

Remark: *1 In the focus position, the environment temperature is +20 °C ± 1.0 °C

Parameters

Model No.			VX3500	VX8500
Image Senor			5M CMOS	20M CMOS
Monitor			24"LCD(XGA:1920x1080)	
Acceptance Lens			Double Telecentric Lens	
Light	Ring		Four-segment illumination(White Light/Green light)	
	Bottom		Telecentric transmission illumination(Green light)	
F.O.V.	Large Field		500x400mm(4 Angles R50)	
	High Precision		430x330mm	
Resolution			0.1μm	
Repeatability of Image Meas.	Wide Field	Without Stitching* ¹	±1μm	±1μm
		With Stitching* ²	±2μm	±2μm
	High Precision	Without Stitching* ¹	±0.5μm	±0.5μm
		With Stitching* ²	±1.5μm	±1.5μm
Accuracy of Image Meas.	Wide Field	Without Stitching* ¹	±5μm	±3μm
		With Stitching* ²	±(7+0.005L)μm	±(5+0.005L)μm
	High Precision	Without Stitching* ¹	±2μm	±1.5μm
		With Stitching* ²	±(4+0.005L)μm	±(3+0.005L)μm
Rotary Chuck	Rotation Angle		Range 360°, Resolution 0.01°	
	Rotation Speed		0.2~2rev/s	
	Max Diameter		Φ60mm	
Height Meas. (Optical Probe) (Optional)	Measuring Range(X*Y)		300*300mm	
	Max Hole/Depth Ratio		1.64	
	Dia. of Beam		Φ100μm(Φ18μm optional)	
	Resolution		0.25μm	
	Z Non-movement	Range(Z)	±2μm	
		Accuracy	±2μm	
	Z Movement	Range(Z)	200mm	
		Accuracy	±(6+0.01H)μm, H is Z movement height in mm	
XY Object Table	X Travel Range		410mm	
	Y Travel Range		310mm	
	Loading Capacity		20kg	
Z-Axis Travel Range			200mm(Motorized)	
Size(LxWxH)			(900x1340x1600)mm	
Weight			950kg	
Input			AC200~240V,50/60Hz, 10A	
Working Environment			Temp.10 °C~35 °C, Humidity 20~80%, Vibration<0.002g, Less than 15Hz	

Remark: *1 In the focus position, the environment temperature is +20 °C ± 1.0 °C

*2 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 2 kg or less;
L is the moving range of the table (mm)

Flash Measuring Machines

Hybrid Series



Description

Composite Flash Measuring Machine Hybrid series is an advanced fully automatic image measuring instrument. It adopts a hybrid architecture of an electric zoom lens and a large double-telecentric lens, offering high precision measurement for the small & complicated features by the electric zoom lens and efficient measurement for the big & easy features by the large double-telecentric lens, so it achieves an optimized combination of precise and efficient measurement.

Composite Flash Measuring Machine Hybrid series can be used in machinery, electronics, molds, injection molding, hardware, rubber, low-voltage electrical appliances, magnetic materials, precision stamping, connectors, connectors, terminals, mobile phones, home appliances, printed circuit boards, medical equipment, watches and clocks, cutting tools, measurement and testing and other fields.

Parameters

Model No.		Hybrid432	Hybrid562	Hybrid682
Travel range	X	400 mm	500 mm	600 mm
	Y	300 mm	600 mm	800 mm
	Z	200 mm	200 mm	200 mm
Structure type		Column	Bridge	Bridge
Base material		Marble	Marble	Marble
Monitor		24" LCD (1920x1080)		
Resolution of glass scale		0.1μm		
Guide rail		Precision linear guide rail		
High-resolution electric zoom lens	Lens	13.3X Electric continuous zoom		
	Magnification	Optical zoom: 0.6~8.0X, Image zoom: 17~232X		
	Image sensor	HD colorful industrial camera		
	Single F.O.V.	1mm×1mm~12mm×12mm		
	Measuring range	360×310mm	410×600mm	610×800mm
	Meas.accuracy (XY)	(1.8+L/200)μm	(2.0+L/200)μm	(2.2+L/200)μm
	Meas.accuracy (Z)	(2.8+L/200)μm		
	Bottom	Telecentric transmission Illumination (Green)		
	Ring	6 rings and 8 segments light (white light)		
	Coaxial light	LED light		
Double telecentric wide F.O.V optical lens	Lens Spec.	Φ100mm double telecentric lens		
	Single F.O.V.	90×90mm		
	Measuring range	440X400mm (4 Angles R50)	480X600mm (4 Angles R50)	580X800mm (4 Angles R50)
	Accuracy of Single F.O.V	±4μm		
	Stitching Accuracy	(4+L/200)μm	(5+L/200)μm	(6+L/200)μm
	Bottom	Telecentric transmission Illumination (Green)		
	Ring	4 segments illumination (White light, 75°), directional ring light (Green light, 0°)		
Max speed	XY	500 mm/s		
	Z	100 mm/s		
Size		530×503×730 mm	850×1240×1600 mm	900×1340×1600 mm
Weight		650 kg	1000kg	1300kg
Loading capacity		25kg	50kg	50kg
Power supply		2000W	2500W	2500W
Motion control		Servo control system		
Software		VisionX Pro		
Input		AC200~240V, 50/60Hz		
Working environment		Temperature 20°C±2°C, humidity 20~80%, vibration<0.002g, lower than 15HZ		

Remark: *1 Image magnification is approximate and depends on monitor size and resolution.


*2 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 5 kg or less; L is the moving range of the table in mm.

*3 It is obtained by using Chotest master gauge in the environment with temperature of 20°C±1°C.


*4 In the focus position, the environment temperature is +20 °C ± 1.0 °C, and the load on the table is 5 kg or less

SuperView W1 3D Optical Surface Profilometer


White Light Interferometry
Nano 3D Surface Form and Roughness



Unique re-establishment algorithm can filter noises of surface of test object.



Super smooth lens



Abraded surface



Interference Lens

Different magnification lenses are selectable for various test objects with smooth or coarse surface



Vacuum Object Table

Vacuum Object Table is specially customized for semi-conducting wafers, so influence from feeble air flowing to test object is eliminated in measurement



Air-Bearing Isolation System

Built-in air bearing isolation system can isolate the vibration. Air pressure of the machine can be supplied by air compressor or inflators.



Sonic Vibration Isolation

The shell is separated from the internal motion unit, which effectively isolates the transmission of sound wave vibration.



Easy Level

Improve the re-establishment accuracy and adjust stripe width by adjusting tilt of object table








Convenient joystick

Easy to control X/Y/Z movement, speed and light source brightness; Emergency stop button










Application

It is used for measurement and analysis of surface roughness and profile of precision components from industries of semi-conductor, 3C Electronics, ultraprecise machining, optical machining, micro-nano materials, micro-electro-mechanical system.

SemiConductor	>>	Cut sheet, coated sheet, wafer IC	>>	Roughness, microcosmic	>>	
3C Electronics	>>	Sapphire screen, glass screen, Ink screen	>>	Roughness, flatness, step height	>>	
Optics	>>	Precision mould, optical lens	>>	Roughness, flatness,profile, radius of curvature	>>	
MicroNano Materials	>>	Film on PET substrate	>>	Film roughness, film thickness	>>	
Tribology	>>	CSM friction/Abraded components	>>	Surface profile, Surface roughness, area, volume	>>	

Application Cases

Measurement and analysis for various products, components and materials' surface form and profile characteristics, such as flatness, roughness, waviness, appearance, surface defect, abrasion, corrosion, gap,hole, stage, curvature, deformation, etc.

Surface formfile  Magnetic diamond head	>>		>>	 Pyramid angle
Profile sizes  Diffractive component	>>		>>	 Profile curve
Surface roughness  Engine blade of airacraf	>>		>>	 Surface roughness

XtremeVision 3D Software

Integration software: Measurement and analysis are operated in the same interface; With pre-set analytic parameters, the software automatically generates measurement data, and achieves rapid CNC measurement.

One-click analysis, multi-file analysis:

After set analytic program, more than 10 files can be analyzed by one click, finally data result and statistical graph are generated automatically

Auto Measurement:


After set measuring ranges & points and related parameters, multi-area can be measured.

Partial measurement:

Can select any area in field of view to be measured.

Stitching Measurement:

After set the measuring range and parameters, large area could be measured by one click automatically.



Lens Specification

Zoom ratio of lens			2.5x	5x	10x	20x	50x	100x
Numerical hole diameter			0.075	0.13	0.3	0.4	0.55	0.7
Optical resolution @550nm(μm)			3.7	2.1	0.92	0.69	0.5	0.4
Depth of focus(μm)			48.6	16.2	3.04	1.71	0.9	0.56
Working distance(mm)			10.3	9.3	7.4	4.7	3.4	2.0
F.O.V. H×V (mm)	Video system 1024x1024	0.5x	3.84x3.84	1.92x1.92	0.96x0.96	0.48x0.48	0.192x0.192	0.096x0.096
		0.75x	2.56x2.56	1.28x1.28	0.64x0.64	0.32x0.32	0.128x0.128	0.064x0.064
		1x	1.92x1.92	0.96x0.96	0.48x0.48	0.24x0.24	0.096x0.096	0.048x0.048

Parameters

Model No*1		W1	W1-pro	W1-Ultra	W1-Lite
Light source		White LED			
Video system		1024×1024			
Objective Lens		Standard: 10X(Optional: 2.5X, 5X, 20X, 50X, 100X)			
Optical Zoom		Standard: 0.5X Optional: 0.375X, 0.75X, 1X			Standard: 0.5X Optional: 0.375X, 0.75X
Standard Field of View		0.98×0.98 mm			
Lens Turret		Standard: Manual 3 holes turret(Optional: Motorized 5 holes turret)			
XY Object Table	Size	320×200mm	300×300mm	320×200mm	220×220mm
	Travel range	140×100mm	200×200mm	140×100mm	100×100mm
	Load capacity	10kg			10kg
	Control method	Motorized			Motorized
Tilt		±5°			±3°
Z Axis	Travel Range	100mm			50mm
	Control method	Motorized			
Z Stroke Scanning Range		10mm			
Surface Form Repeatability*2		0.1nm			
Roughness RMS Repeatability*3		0.005nm			
Step Height Measurement*4		Accuracy: 0.3%; Repeatability: 0.08%(1σ)			Accuracy: 0.5% Repeatability: 0.1%(1σ)
Scanning Speed@0.1nm resolution		1.85μm/s	1.85μm/s	8μm/s	1.85μm/s
Reflectivity of Test object		0.05% ~ 100%			
Weight		<160 kg			50 kg
Size(L*W*H)		700×606×920mm			440×330×700mm
Operating Environment	Temperature	15°C~30°C, fluctuation <1°C/15min			
	Humidity	5%~95% RH, no condensation			
	Vibration	VC-C or better			
	Software Noise Evaluation*5	3σ≤4nm			
	Compressed Air	0.6Mpa oil-free, water-free, 6mm diameter of hose			
	Power Supply	AC100~240V, 50/60Hz, 4A, 300W			
	Other	No strong magnetic field, No corrosive gas			

*1 W1 is the standard model of 3D Optical Surface Profilometer; W1-pro has larger stage size and travel range.

W1-Ultra has greatly improved the scanning speed compared to W1.

*2 Use EPSI mode to measure Sa 0.2nm silicon wafer in the laboratory environment; Single stripe, 80um filter for full field of view

*3 Measure Sa 0.2nm silicon wafer in a laboratory environment according to the ISO 25178.

*4 Measure standard 4.7μm steps height block in a laboratory environment according to the ISO 5436-1:2000

*5 When the software noise evaluation is $4\text{nm} \leq 3\sigma \leq 10\text{nm}$, the Roughness RMS repeatability is revised down to 0.015nm, the Step height measurement accuracy is revised down to 0.7%, and the step height measurement repeatability is revised down to 0.12%; When the software noise evaluation is $3\sigma > 10\text{nm}$, the environment does not meet the requirement for usage of the equipment, and need to change the site.

SuperView W3

3D Optical Surface Profilometer

Large-scale microscopic 3D form and roughness

- Large table
- Applicable for 12" wafer
- One-key automatic measurement



■ Dedicated Functions for Semiconductor Field

- Measure profile trenches after laser grooving in the dicing process.
- Measure film step-height of wafer ranging from 1nm~1mm.
- Measure roughness of silicon cut sheet after grinding process, and can measure dozens of small areas to obtain the average value by one click.
- Support 6", 8" and 12" wafer measurement, and easy switch between 3 sizes of vacuum chucks by one click automatically.

Parameters

Model No.		SuperView W3	
Size		(1000×900×1500) mm	
Weight		500 kg	
Light Source		White LED	
Video System		1024×1024	
Objective Lens		10×,(2.5×,5×, 20×,50×,100×)	
Optical Zoom		0.5×,(0.75×, 1×, 0.375×)	
Standard F.O.V.		0.98×0.98mm	
Lens Turret		Motorized 5 holes turret	
XY Object Table	Size	450×450mm	
	Travel Range	300×300mm	
	Load Capacity	10kg	
	Control Method	Motorized	
Tilt		±6°Motorized	
Z Axis	Travel Range	100mm	
	Control Method	Motorized	
Z- Stroke Scanning Range		10mm	
Z Resolution		0.1nm	
Reflectivity of Object		0.05%~100%	
Roughness RMS Repeatability ^{*1}		0.005nm	
Step Height Measurement	Accuracy ^{*2}	0.3%	
	Repeatability ^{*2}	0.08% 1σ	
Environmental requirement			
1	Operating environment: No strong magnetic field	4	Environmental vibration: VC-C or better
2	Working temperature: 15°C~30°C fluctuation <2 °C/60min	5	Compressed air: 0.6Mpa oil-free, water-free
3	Relative humidity: 5%~95% RH, no condensation	6	Power: 330W

*1 Measure Sa 0.2nm silicon wafer in a laboratory environment according to the ISO 25178

*2 Measure standard 4.7μm steps height block in a laboratory environment according to the ISO 5436-1:2000

SuperView W5

5-Axis

Auto 3D Optical Surface Profilometer



Description

SuperView W5 is mainly used for high-precision measurement of surface roughness and waviness of irregular workpieces. Equipping a 5-axis object table(X/Y/Z axis, tilt & rotation), it can achieve rapid positioning through imported 3D model. Then the measurement head can automatically scan the specified position and software obtains test data including 2D/3D topography, roughness, waviness, etc.

Parameters

Model No.		SuperView W5
Light Source		White LED
Video System		1024×1024
Objective Lens		10×, 20×
Field of View		0.98×0.98 mm (10×)
XY Object Table	Size	400×400mm
	Travel Range	300×300mm
	Load Capacity	20kg
	Control Method	Motorized
Rotary Stage	Tilt	±90°
	Rotation	360°
	Load Capacity	10kg
	Control Method	Motorized
Z Axis	Travel Range	100mm
	Control Method	Motorized
Z Stroke Scanning Range		10 mm
Z Resolution		0.1nm
Roughness RMS Repeatability* ¹		0.005nm
Step Height Measurement	Accuracy* ²	0.5%
	Repeatability* ²	0.1%
Working Temperature		0~40°C, fluctuation ≤2°C/h
Working Relative Humidity		≤70%

*1 Measure Sa 0.2nm silicon wafer in a laboratory environment according to the ISO 25178.

*2 Measure standard 4.7μm steps height block in a laboratory environment according to the ISO 5436-1:2000

SuperView WX100

White Light Interferometry Probe

In-line roughness and 3D profile inspection

ZSTOP

Double anti-collision protection

Software ZSTOP and hardware electronic sensors. Besides it could accept external anti-collision electronic signals.



Four DOF motorized tilt

Provides an electric tilt adjustment design with four degrees of freedom in pitch and yaw, which greatly reduces the manufacturing difficulty of the customer's measuring stage.



Z travel range 30mm

Capable to measure samples with different height. Users need not to prepare a moving Z axis



SDK




Provide the software package for customers to carry out secondary development, so that customers can develop the software program to control the probe for automatic measurement and analysis.

Functions


- Measurement function: it can realize high precision Z scanning of sample surface and obtain 3D image.
- Analysis function: It can obtain 2D and 3D data such as surface roughness, micro-nano-level contour size, etc.
- Programming function: Support pre-configured data processing and analysis tool steps, one-click to complete the whole process from measurement to analysis.
- Batch analysis: Data processing and analysis templates can be customized according to the customer demands, and one-click batch analysis can be realized for the same type of parameter data

Application

Semiconductor, polished silicon wafer, thin silicon wafer, wafer IC



3C electronics, sapphire glass roughness, metal shell mold defects, glass screen height difference




Parameters

Model No.		SuperView WX100
Light Source		White LED
Video System		1024×1024
Objective Lens		10×(20×,50×)
F.O.V		0.98×0.98mm
Lens Turret		Single hole
Size		230×200×380mm
Tilt		±2° Motorized
Z Travel Range		30mm
Z Scanning Range		10mm(Depend on Lens)
Z Resolution		0.1nm
Reflectivity of Test Object		0.05%~100%
Roughness RMS Repeatability*1		0.01nm
Step Height Measurement	Accuracy*2	0.5%
	Repeatability*2	0.1% 1σ

*1 Measure Sa 0.2nm silicon wafer in a laboratory environment according to the ISO 25178.

*2 Measure standard 4.7μm steps height block in a laboratory environment according to the ISO 5436-1:2000

VT6000 Series Confocal Microscope



VT6100




VT6200



VT6300

Description

Confocal Microscope VT6100 is dedicated for micro-nano level measurement of various precision components and material surfaces. It can measure the surface of various objects from smooth to rough, low reflectivity to high reflectivity, and the roughness, flatness, micro-geometric profile, curvature, etc. Total more than 300 kinds of 2D and 3D parameters as per four major domestic and foreign standards ISO/ASME/EUR/GBT are provided as evaluation standards



Features

1. High precision and high repeatability

- 1) Based on the rotating confocal optical system, combined with high stability structural design and excellent 3D reconstruction algorithm, the measurement system is jointly composed to ensure the high measurement accuracy of the instrument.
- 2) The unique shock isolation design can reduce the vibration noise of the bottom surface, the instrument is stable and reliable in most environments, and has good measurement repeatability

2. All-in-one operation of measurement analysis software

- 1) The measurement and analysis are operated on the same interface without switching, and the measurement data is automatically counted, realizing the function of rapid batch measurement
- 2) The visualization window is convenient for users to observe the scanning process in real time
- 3) Combined with the automatic measurement function of the custom analysis template, the multi-region measurement and analysis can be automatically completed
- 4) Five functional modules of geometric analysis, roughness analysis, structural analysis, frequency analysis and functional analysis.
- 5) One-key analysis, multi-file analysis, free combination analysis items are saved as analysis templates, one-key analysis of batch samples, and data analysis and statistical chart functions are provided
- 6) More than 300 kinds of 2D and 3D parameters can be measured according to ISO/ASME/EUR/GBT


3. Precision joystick

The joystick integrated with the displacement adjustment functions in the three directions of X, Y, and Z can quickly complete the pre-measurement works such as stage translation and 2-way focusing etc.


4. Double anti-collision protection measures

In addition to the software ZSTOP setting the lower limit of the Z-direction displacement for anti-collision protection, a mechanical and electronic sensor is designed on the Z-axis. When the lens touches the surface of the sample, the instrument automatically enters an emergency stop state to protect the instrument to the greatest extent and reduce the risk of human operation


Application




Laser hole




Patterned Wafer




Microlens matrix




Taper hole



Optical lens




Diamond drill




Conductive ceramics




Paper fiber



Ultra-precision metal tip




PCB



Gold plated micro-holes



Grid line of solar plate



Parameters

Model No.		VT6100	VT6200	VT6300
Travel Range	X	100mm	200mm	300mm
	Y	100mm	200mm	300mm
	Z	100mm	100mm	100mm
Size		520×380×600mm	720×580×1500mm	1000×900×1500mm
Weight		50kg	400kg	500kg
Principle		Spinning disk confocal optical system		
Objective lens		50×(Optional: 10×, 20×, 100×)		
Field of View		120×120 μm~1.2×1.2 mm		
Step Height Measurement	Repeatability(1σ)	12nm		
	Accuracy*1	± (0.2+L/100) μm		
	Display Resolution	0.5nm		
Width Measurement	Repeatability(1σ)	40nm		
	Accuracy*2	± 2%		
	Display Resolution	1nm		
XY Object Table	Load Capacity	10kg		
	Control Method	Motorized		
Z-Axis Stroke Scanning Range		10 mm		
Lens Turret		Motorized 5 holes turret		
Light Source		White LED		
Operating Environment	Power Supply	100~240V AC, 50/60Hz, 2A, Power 300W		
	Working Temp.	15℃~30℃, fluctuation < 2℃/60min		
	Humidity	5%~95%RH, no condensation		
	Vibration	VC-C or better		
	Other	No strong magnetic field		

*1 Measure standard 4.7μm steps height block by 50× Objective lens in a laboratory environment

*1 Measure standard engraved line block by 50× Objective lens in a laboratory environment

MX 3200

Microscopic Measuring Machine



Description

Microscopic measuring machine MX3200 achieves wide-range measurement of tiny features by combining microscopic imaging with traditional video measurement. Equipped with a motorized turret, it can measure various microscopic 2D sizes by switching different lens, including points, lines, circles and geometric tolerances, etc.

Application



Parameters

Model No.		MX3200		
Objective Lens		10×	20×	50×
Image Sensor		Industrial Camera		
Monitor		24" LCD (XGA: 1920x1080)		
Lens Turret		3 Holes Manual(Optional: 5 holes motorized)		
Single F.O.V.		0.98×0.98mm	0.49×0.49mm	0.196×0.196mm
Lateral Resolution* ¹		2μm	1μm	0.4μm
Accuracy* ²	Single F.O.V.	±0.3μm	±0.2μm	±0.1μm
	Motion Axis Ex/Ey	±(2.0+0.02 L)μm		
Repeatability in Single F.O.V.* ³		±0.1μm	±0.1μm	±0.05μm
Height Meas.* ⁴	Accuracy	±(3.0+L/100)μm		
	Repeatability	±1μm		
Travel range	X	210mm		
	Y	110mm		
	Z	75mm		
Resolution of Glass Scale		0.1μm		
Light	Surface Light	Coaxial light		
	Back Light	Telecentric transmission illumination(Green Light)		
Height Meas. (Optical Probe) (Optional)	Max Hole/Depth Ratio(h/φ)	1.64		
	Range(Z)	±2mm		
	Accuracy	±2.0μm		
Software		VisionX		
Max Measurement Speed	XY	80 mm/s		
	Z	25 mm/s		
Size(LxWxH)		531×455×761mm		
Weight		74kg		
Loading Capacity		5kg		
Power Supply		AC100~240V,50/60Hz,2A Power 300W		
Working Environment		Temp.10°C~35°C, Humidity 20~80%, Vibration<0.002g, Less than 15Hz		

*1 In the focus position, measure resolution panel when the environment temperature is +20 °C ± 1.0 °C.

*2 In the focus position, measure Micro-Nano standard specimen when the environment temperature is +20 °C ± 1.0 °C.

*3 In the focus position, measure Micro-Nano standard specimen when the environment temperature is +20 °C ± 1.0 °C.

*4 It is the Z-axis mechanical accuracy, and the accuracy of actual height measurement by focusing depends on the surface of the workpiece.



Laser Tracker GTS Series

Large-scale space measurement



Integrated Measurement Head

Powerful CPU processing capability, compact control system are built into the laser head, and this integrated design greatly reduces the product volume and number of connection cables



Automatic Locking

The camera will automatically search for the SMR in a certain area when the beam interrupts, and automatically lock the SMR after find it. The whole process does not require human operation.



HiADM

Absolute Distance Meter(ADM) and laser interferometer(IFM) fusion technology (HiADM) ensures excellent measurement accuracy and realizes Re-establish Beam Interruptions.



Integrated Environmental Weather Station

The integrated environmental weather station automatically monitors the environmental meteorological parameters, and compensates the influence of temperature, air pressure and humidity in real time.



MultiComm Communication

The instrument and computer can communicate with each other through hardware trigger, wired network or WIFI. The max measurement data output speed is 1000 points/second



Portable

The laser head and accessories are packed well in portable boxes, making it easy to transport between different work sites.



IP54 Protection

IP54 protection level ensures that the host is protected from dust and other pollutants, and has strong environmental applicability.



Steady Tripod

The stable triangular support system avoids the loss of accuracy caused by environmental vibrations

6D Attitude Probe iProbe

- Sensing fusion technology of machine vision and gravity alignment to measure spatial attitude
- It can measure geometric structures of holes' internal and hidden features
- Dual-probe design, more efficient when measuring complex features
- Wireless transmission, easy to carry



6D Attitude Smart Sensor iTracker

- The attitude sensor automatically follows and locks the laser beam, which has high measurement flexibility
- The pitch angle and yaw angle are not limited by the receiving angle of the optical receiver.
- Simple interface connection, easy to install on machine tools or robots, high repeatability and precision
- Dedicated band laser beam and filter design, not sensitive to ambient light
- The highest sampling speed is 200 points/second



Application



Airplane Assembly



Train Assembly



Nuclear Generator Assembly



Vessel Assembly



Wind-Driven Generator Assembly



Rocket Assembly



Hydroelectric Generator Assembly



Robot Arm Calibration



TBM Assembly



Car Assembly




Large Weapon Assembly




Large Machine tool Calibration

Spatial Measurement Software SpatialMaster



- Traceability, faithfully record the measurement information of all measurement points of all instruments
- Rich geometry construction methods and accurate fitting algorithms, certified by Gauss and Chebyshev double PTB
- Multiple registration and alignment methods such as optimal fitting, sequential registration, and comprehensive alignment
- Provides powerful analysis functions, geometric relationship measurement functions, including professional GD & T evaluation
- The convenient monitoring function can provide efficient assembly and adjustment services for the actual production assembly process
- Self-controllable, visible and available report format, meeting various report format requirements
- Automatic measurement, In-line measurement, Guide point measurement, Batch point measurement functions improve measurement efficiency
- Support multi-station simultaneous measurement, and can carry out unified spatial measurement and analysis of multi-tracker multilateral method.
- Provide SDK interface, support user independent programming

Robot Calibration Software RobotMaster



RobotMaster Software

The RobotMaster kit provides an absolute position accuracy calibration and performance test for industrial robots. RobotMaster supports not only enhanced solutions based on 6D attitude smart sensors, but also supports economic solutions based on SMR.

Robot Calibration Software

According to the DH parameters of the robot, the robot calibration mathematical model is established, and the robot zero position calibration, the robot DH parameter calibration, and the robot TCP center point accuracy calibration are performed. Without changing any structure and hardware size of the existing robot, the absolute pose accuracy of the robot can be effectively improved through the robot calibration software.

Robot performance testing software

According to the ISO 9283 industrial robot performance specification and its experimental method, the robot performance test is completed. The test content includes: robot pose accuracy, pose repeatability, multi-directional pose accuracy change, distance accuracy, distance repeatability, position stabilization time, position overshoot, pose characteristic drift, interchangeability, trajectory accuracy, trajectory repeatability, corner deviation, trajectory velocity characteristics, static compliance, etc.

GTS3000 Series Parameters

Model No.		GTS3300	GTS3600	GTS3800
Basic Spec.	Head Size	220×280×495mm	220×280×495mm	220×280×495mm
	Head Weight	21.0Kg	21.3Kg	21.3Kg
	Controller	Integrated		
	Laser Generator* ¹	633nm, 1mW/CW Class 2		
	Support 6D	No		
	Protection Level	IP54		
Measuring Range	Max Distance(Radius)	30m	60m	80m
	Horizontal	±360°	±360°	±360°
	Vertical	-145°~+145°	-145°~+145°	-145°~+145°
Accuracy* ²	Volumetric Accuracy	15μm+6μm/m	15μm+6μm/m	15μm+6μm/m
	IFM Accuracy	0.5μm/m	0.5μm/m	0.5μm/m
	ADM Accuracy	10μm(Entire range)	10μm(Entire range)	10μm(Entire range)
	Level Accuracy	2.0"	2.0"	2.0"
Data Output Rate		1000points/sec.	1000points/sec.	1000points/sec.
Communication	Cable Connection	TCP/IP(Cat5)		
	Wireless Connection	WLAN(IEEE 802.11N)		
Environmental	Operating Temperature	0°C~40°C		
	Altitude	-500~+3500m		
	Relative Humidity	0~95%. non-condensing		
Power Supply		220±10%VAC, 50/60Hz, 4A, 220W		

*1 According to IEC60825-1(2014-5), it meets the radiation performance standard.

*2 The accuracy index is the maximum permissible error (MPE), using the standard 1.5''SMR, excluding the influence of air temperature variations.

Parameters of 6D Attitude Probe

6D Attitude Probe iProbe		
Measuring Range	Max Range(Radius)	30m
Basic Spec.	Weight* ¹	0.68kg
	Size* ²	93×90×178mm
Accuracy	Spatial Accuracy* ³	60μm+6μm/m
Measuring Arm	Ball Diameter	3mm、6mm
	Arm Material	Li-ion battery
	Arm length	40mm, 100mm, 200mm, 400mm
Communication	Max Transmission Speed	100Hz
	Connection Type	WIFI
Power supply	Type	Li-ion battery
	Working Duration	≥8 hours

*1 Includes battery and 100mm measuring arm;

*2 Does not include measuring arm;

*3 Uses 100mm measuring arm.

GTS6000 Series Parameters

Model No.		GTS6300	GTS6600	GTS6800
Basic Spec.	Head Size	220×280×495mm	220×280×495mm	220×280×495mm
	Head Weight	21.0Kg	21.3Kg	21.3Kg
	Controller	Integrated		
	Laser Generator*1	633nm, 1mW/CW Class 2		
	Support 6D	Yes		
	Protection Level	IP54		
Measuring Range	Max Distance(Radius)	30m	60m	80m
	Horizontal	±360°	±360°	±360°
	Vertical	-145°~+145°	-145°~+145°	-145°~+145°
Accuracy*2	Volumetric Accuracy	15μm+6μm/m	15μm+6μm/m	15μm+6μm/m
	IFM Accuracy	0.5μm/m	0.5μm/m	0.5μm/m
	ADM Accuracy	10μm(Entire range)	10μm(Entire range)	10μm(Entire range)
	Level Accuracy	2.0"	2.0"	2.0"
Data Output Rate		1000points/sec.	1000points/sec.	1000points/sec.
Communication	Cable Connection	TCP/IP(Cat5)		
	Wireless Connection	WLAN(IEEE 802.11N)		
Environmental	Operating Temperature	0°C~40°C		
	Altitude	-500~+3500m		
	Relative Humidity	0~95%. non-condensing		
Power Supply		220±10%VAC, 50/60Hz, 4A, 220W		

*1 According to IEC60825-1(2014-5), it meets the radiation performance standard.

*2 The accuracy index is the maximum permissible error (MPE), using the standard 1.5"SMR, excluding the influence of air temperature variations.

Parameters of 6D Attitude Sensor

6D Attitude Sensor iTracker		
Measuring Range	Max Range(Radius)	30m
Basic Spec.	Weight	1.32kg
	Size	105×98×168mm
Measuring Range	Pitch	-55°~+60°
	Yaw	±180°
	Roll	±360°
Accuracy	Attitude Angular Accuracy	0.03°
	Repeatability	0.005°
Communication	Max Transmission Speed	200Hz
	Connection Type	30m cable
Power supply		From laser tracker

Laser Interferometer SJ6000

Calibration of Guide Rail



Prism Modules




Laser interferometer is recognized as a high precision, high sensitive measuring method by applying light wavelength as criterion, and is widely used in high-end manufacturing industries.

Laser interferometer SJ6000 insists of high-frequency Helium-Neon laser generator from an USA supplier, high-precision environmental compensation modules, high-precision laser interference signal processing system, high-performance computer control system. By applying with thermal frequency stabilization technology of laser dual-longitudinal mode and geometric parameters interference optical path design, SJ6000 can output long-term stable and high-precision (0.05ppm) laser quickly (about 6 minutes) which has powerful anti-interference performance. With different prism modules, it can measure linearity, angle, straightness, Flatness and perpendicularity, besides it can also analyze dynamic characteristics.

Functions

1. Calibrate motion accuracy of guide rail quickly and accurately.
2. Measure and analyze many kinds of dynamic parameters, such as displacement, velocity, acceleration and amplitude frequency.
3. Built-in variety of general standards of machine tools.

Application



Linear meas. of machine tool



Linear meas. of stage module



Lab length reference



Linear meas. of machine tool



Angle meas. of stage module



Angle meas. of DC motor



Parallelism meas. of two guide rails



Straightness meas. of equipment



Flatness meas. of Granite table



Perpendicularity meas. of CMM




Perpendicularity meas. of equipment



Twin guide rails meas. of equipment

Software



Dynamic Measurement Application

Time based

Motion performance evaluation

- * Control parameter test and setting of motion controller PID
- * Stability test and evaluation after high-speed motion
- * Small steps test of high-performance motion controller

Vibration monitoring

- * Scanning application:

Applied for the situation when positioning accuracy is not important but constant speed is critical for high quality imaging.

- * Machine tool applications:

Applied for the situation when slow and smooth contour movement of cutting tool is critical for high quality machining.

Vibration frequency analysis

- * Vibration frequency analysis of the measured object
- * FFT fast Fourier transform analysis

Distance based

In distance-based dynamic measurement, laser interferometer SJ6000 "flies" along the axis, that means SJ6000 samples data at designated points without stopping

Pulse Trigger Mode

Pulse trigger CT70 is compatible with glass scales, encoders and controllers. Equipped with Pulse trigger CT70, laser interferometer SJ6000 can sample data in pulse trigger mode. Even if the axis does not stop, laser interferometer SJ6000 could sample data at designated points or continuously sample data




Pulse trigger CT70

Parameters

System parameters:				
1. Measuring method: single frequency				
2. Laser frequency accuracy: 0.05ppm				
3. Dynamic capture rate: 50kHz				
4. Warm-up time: about 6 min				
5. Operating temperature: (0~40)°C				
6. Environment temperature: (0~40)°C, humidity: 0-95%				
7. Storage temperature: -20°C~70°C				
Environmental sensors:				
1. Atmospheric temperature sensor : $\pm 0.1^{\circ}\text{C}$ (0~40)°C, resolution: 0.01°C				
2. Material temperature sensor: $\pm 0.1^{\circ}\text{C}$ (0~40)°C, resolution: 0.01°C				
3. Atmospheric humidity sensor: $\pm 5\%$ (0~95%)				
4. Atmospheric pressure sensor: +0.1kPa (65~115)kPa				
Linear measurement:				
1. Measuring range: (0~80)m				
2. Measuring accuracy: 0.5ppm (0~40)°C				
3. Measuring resolution: 1nm				
4. Maximum measuring speed: 4m/s				
Angle measurement:				
1. Axial range: (0~15)m				
2. Measuring range: $\pm 10^{\circ}$				
3. Measuring accuracy: $\pm (0.02\%R + 0.1 + 0.24M)^{\circ}$ (R is indicating value, unit: " ; M is measured length in meters)				
4. Measuring resolution: 0.1"				
Flatness measurement:				
1. Axial range: (0~15) m				
2. Flatness measuring range: ± 1.5 mm				
3. Measuring accuracy: $\pm (0.2\%R + 0.02M^2)$ μm (R is indicating value in μm ; M is measured length in meters)				
4. Substrate size: 180mm adjustable, 360mm adjustable				
5. Measuring resolution: 0.1 μm				
Straightness measurement:				
Item	Axis range	Measuring range	Accuracy	Resolution
Short straightness	(0.1~4)m	$\pm 3.0\text{mm}$	$\pm (0.5 + 0.25\%R + 0.15M^2)$ μm	0.01 μm
Long straightness	(1~20)m	$\pm 3.0\text{mm}$	$\pm (5.0 + 2.5\%R + 0.015M^2)$ μm	0.1 μm
Note: R is indicating value in μm ; M is measured length in meters				
Perpendicularity measurement:				
Item	Axis range	Measuring range	Accuracy	Resolution
Short straightness	(0.1~3)m	$\pm 3.0\text{mm}$	$\pm (2.5 + 0.25\%R + 0.8M)$ $\mu\text{m}/\text{m}$	0.01 μm
Long straightness	(1~15)m	$\pm 3.0\text{mm}$	$\pm (2.5 + 2.5\%R + 0.08M)$ $\mu\text{m}/\text{m}$	0.01 μm
Note: R is indicating value in μm ; M is measured length in meters				
Rotary axis measurement:				
1. Measuring range of angle: 0~360°				
2. Max axis rotation speed: 10rpm				
3. Pitch accuracy of precision turntable: $\pm 1''$				
4. Resolution : 0.1"				

WR 50 Rotary Axis Calibrator



Measurement Principle

Equipped with Rotary axis calibrator WR50 and Angle prism, Laser interferometer SJ6000 is capable to calibrate rotary axis 0~360°. Rotary axis calibrator WR50 is installed to the rotary axis as an angle master.

Parameters

Model No.	WR50	Weight	1.9kg
Measuring range	(0~360)°	Height	148mm
Measuring range	±1"	Diameter	112mm
Resolution	0.1"	Communication type	Bluetooth
Max axis rotation speed	10rpm	Power supply	Li-battery
Max tracking speed	2rpm		


Application



Rotary axis measurement of CNC



Electric spindle measurement of CNC



Swing axis measurement of CNC



Angle measurement of CNC index plate




Angle measurement of turntable



Angle measurement of CNC turntable

Software



Eccentric Axis Measurement


Equipped with angle prism, precision turntable WR50, dedicated jig and dedicated software, SJ6000 is capable to calibrate eccentric axis rotation accuracy.

Eccentric axis meas. kit:

1. Magnet, 3pcs


2. 90° Jig

3. Dedicated software




Measurement Principle

The measurement principle is to use the synchronous movement of the object table and the main spindle, as shown in the figure below. It is important to make sure that angle prism should be always aligned with WR50.



Software Settings



Application



Eccentric axis measurement

Wireless Ballbar MT21

Fast Diagnosis for Machine Tools

MT21 Wireless Ballbar is a simple, fast, economical and efficient solution to diagnose performance of machine tools, and helps to improve the machining quality of machine tools.



Feature

Simple, Fast

The measurement software with guided operation can generate the machine running program automatically. With simple setting, the round track test on three orthogonal planes can be completed in 10~15 minutes.

Powerful Function

Comprehensive diagnosis report provides a full and professional assessment of machine performance. Taking 360 degree measurement at the XY plane as an example, it can analyze: backlash X, backlash Y, reverse jump X, reverse jump Y, lateral gap X, lateral gap Y, period error X, period error Y, servo Mismatch, perpendicularity, straightness X, straightness Y, proportional mismatch, scale error X, scale error Y, thread pitch X, thread pitch Y, feed rate, center offset X, center offset Y, position tolerance, the best fitting radius, roundness.

Wireless

Data is transmitted to the laptop computer via Bluetooth in real time.

Software

MT21 software with guided operation can implement the round track test on three orthogonal planes quickly and simply. After measurement, software calculates the overall measurement values (roundness, roundness deviation) of the positional accuracy automatically, then generates the analysis report with the graphic format according to GB17421-4, ISO230-4. MT21 achieves the real spatial diagnosis for machine tools.



Error Analysis Report


Parameters

Communication: Bluetooth(Typical 10m)
Power supply: Li-battery
Resolution: 0.1μm
Measuring accuracy: $\pm(0.7+0.3\%L)\mu\text{m}$
Measuring range: $\pm 1.0\text{mm}$
Sensor range: $\pm 2.0\text{mm}$
Sample rate: 1000Hz
Working Temperature: (0~40)°C
Size: 120×26×21mm


Configuration

1. MT21 Wireless Ballbar	1pc
2. Master gauge	1pc
3. Offset setting ball	1pc
4. Centric holder	1pc
5. Tool cup	1pc
6. Extension bar 50, 100, 150mm	1pc of each
7. Software	
8. Portable suitcase	
9. User Manual	


Application



Roundness inspection of machine tools



Contact Measurement Instruments



SJ5780 Series Intelligent Profilometer


Two-Sided Scanning
Dedicated for Threaded workpieces



Application



Coaxiality of lead screw



Thread gauge



Trapezoidal lead screw



Ballscrew



Cylindrical workpiece



Gear

Features

1. Two-sided profile scanning function

It obtains profile of object by scanning the surface with T-shaped stylus, then software can calculate the 2D sizes and GD & T based on the profile.

2. Thread scanning function

It can scan ordinary thread ring/plug gauges, tapered thread ring/plug gauges, plain ring/plug gauges, trapezoidal thread, sawtooth thread, multi-head threaded workpieces, lead screws, etc. Then the software can analyze their comprehensive parameters such as internal and external diameter, profile parameters, etc.

Parameters

Model No.			SJ5780-200	SJ5780-300	SJ5780-400
Basic Spec.	Measuring Range	X	0~235mm	0~325mm	0~400mm
		Z	0~235mm	0~325mm	0~400mm
	Min Resolution		0.001μm		
	Scanning Speed		0.1~2mm/s		
	Measuring Force		10~150mN		
	Max Slope		Uphill 78°, downhill 87°		
	Y Direction Object Table		Travel range 25mm, Overall height 85mm(Motorized table is optional)		
Thread Meas.	Thread Measuring Range		Internal: M3~M200, External: M3~M200(Determined by optional jigs)		
	Accuracy(Maj., Pit., Min. Diamter)		≤±(4+L/100) μ m, L is measured length in mm		
	Accuracy(Thread Pitch)		≤±(1 +L/100) μ m, L is measured length in mm		
Profile Meas.	Diameter Measuring Range		Internal: φ3~φ200, External: φ3~φ200(Determined by optional jigs)		
	Diameter Measuring Accuracy		≤±(3+L/100) μ m, L is measured length in mm		
	Profile Degree Accuracy		≤±(2 +L/100) μ m, L is measured length in mm		
Roughness Meas. (Optional)	Roughness Parameters		R Roughness : Rp,Rv,Rz,Rc,Rt,Ra,Rq,Rsk,Rku,RSm,RPc,Rdq,Rdc,Rmr,Rmax,Rpm, tp,Htp,Pc,Rda,Ry,Sm,S,Rpc,RzJ ; Key Roughness : Rk,Rpk,Rvk,Rpkx,Rvkkx,Mr1,Mr2,A1,A2,Vo ; Profile : Pa,Pq,Pt,Pz,Pp,Pv,PSm,PSk,Pku,Pdq,Pdc,Pc,PPc,Pmr,Rad,PzJ,Pmax ; Waviness of Profile : Wa,Wq,Wt,Wz,Wp,Wv,WSm,Wsk,Wku,Wdq,Wdc,Wmr,Wpc,Wc ; Motif : R,AR,W,AW,Rx,Wx,Wte ;		
	Ra Measuring Range		Ra0.012μm~Ra12.5μm		
	Filter		2RC filtering, Gaussian filtering and Zero phase filtering		
	Sampling Length		0.008, 0.08, 0.25, 0.8, 2.5, 8.0, 25mm		
	Evaluation Length		Automatic calculation		
	Cutoff Wavelength		0.25/0.8/2.5(mm) or User-defined cut-off		
Size(L×W×H)			1200×500×980mm	1200×500×1180mm	1200×500×1180mm
Weight			100kg	200kg	200kg

SJ5720-OPT Series Profilometers for Optics Surface



SJ5720-OPT100



SJ5720-OPT200

Application



Lens



Intraocular lens mold




Vehicle Lens



Infrared lens



Optical mold



Lens

Description

The SJ5720-OPT series is capable to measure both surface roughness and profile after once scanning. Moreover, there is a dedicated software module for measurement and analysis of large aspheric surface, so this series is an ideal measurement solution for the optical lens industry.


It can also be used for profile and roughness measurement for large curved surface, such as bearings, artificial joints, precision molds, gears, blades, etc. Consequently, it is widely used in precision machining, automobiles, bearings, machine tools, molds, precision hardware and other industries.

Features

1. Evaluate profile and roughness parameters at the same time after once scanning
2. High precision, high stability, and high repeatability
3. Aspheric optical software module
4. Intelligent management and advanced software analysis system
5. Intelligent protection system during scanning
6. Flexible manual control
7. High stability vibration isolation system

Software

- Professional aspheric surface measurement software can analyze all aspheric surface
- parameters. There are some self-checking parameters in the software, so the correctness of the input formula can be determined by self-checking.



Aspheric surface measurement interface

Parameters

Model No.			SJ5720-OPT100
Profile Measurement	Measuring Range	X	0~100mm
		Z	0~300mm
		Z1	±6mm (Optional: ±12mm)
	Resolution		0.001um
	Accuracy	Z1*1	≤± (0.5+0.03 H) μm (H, mm)
		Pt*2	Pt≤0.2μm
		Standard Ball*3	≤± (1+R/20) μm (R, mm)
		Angle*4	≤± 1'
	Moving Speed	X	0~20mm/s
		Z	0~20mm/s
	Scanning Speed		0.05~5mm/s
	X Straightness*5		≤0.15μm/100mm
Measuring Force		0.5mN, 0.75mN, 1mN, 2mN, 3mN(Adjustable)	
Roughness Measurement	Ra Masurement Range		Ra0.012μm~Ra12.5μm
	Accuracy*6		Ra0.012μm ~ Ra3.2 μm: ≤±(3nm+2.0%A),A(Ra) μm Ra3.201μm ~ Ra12.5μm : ≤±(3nm+3.5%A),A(Ra) μm
	Repeatability (1δ)*7		1δ≤1nm
	Measurement Residual*8		Rq≤3nm
	Roughness Parameters		R Roughness : Rp,Rv,Rz,Rc,Rt,Ra,Rq,Rsk,Rku,RSm,RPc,Rdq,Rdc,Rmr,Rmax,Rpm, tp,Htp,Pc,Rda,Ry,Sm,S,Rpc,RzJ; Key Roughness : Rk,Rpk,Rvk,Rpkx,Rvkx,Mr1,Mr2,A1,A2,Vo; Profile : Pa,Pq,Pt,Pz,Pp,Pv,PSm,Psk,Pku,Pdq,Pdc,Pc,PPc,Pmr,Rad,PzJ,Pmax; Waviness of Profile : Wa,Wq,Wt,Wz,Wp,Wv,WSm,Wsk,Wku,Wdq,Wdc,Wmr,Wpc,Wc Motif : R,AR,W,AW,Rx,Wx,Wte; Standards : GB/T 3505-2009,ISO 4287:1997,ISO13565-2:1996,ASME B46.1-2002, DIN EN ISO 4287:2010,JIS B 0601:2013,JIS B 0601-1994, JIS B 0601-1982,ISO 1302:2002
	Aspheric Masurement Parameters		Micro profile parameters: Pt, Pa, Fig;Inclination parameters: Smx, Smn ; Horizontal axis angle parameter: Tilt; Distance parameters between the optical axis and the contour: Xp , Xv , Xt ; Root mean square roughness parameter: RMS; Slope parameters: Slpe mx , Slpemx (x), Slperms; Vertex radius error parameter: Radius Err
	Filter		Gaussian filter, 2RC filter, zero phase filter
	Sampling Length		0.008, 0.08, 0.25, 0.8, 2.5, 8.0 or 25mm Selectable
	Evaluation Length		Auto calculation
	Size(L×W×H)		
Weight			195kg

*1 The accuracy is based on the measurement standard gauge block.

*2 The accuracy is based on the Pt test of standard ball smaller than diameter 25mm.

*3 The accuracy is based on the verification of the Φ 50mm standard ball with the arc exceeds 90 degrees.

*4 The accuracy is based on the measurement of the angle of polygonal prism.

*5 The accuracy is based on the measurement of optical flat.

*6 The accuracy is based on the measurement of standard roughness block.

*7 The repeatability is based on the measurement of 0.1-0.2μm square wave roughness block and standard step height block.

*8 The accuracy is based on the measurement of 1nm level roughness block and optical flat.

Parameters

Model No.			SJ5720-OPT200
Profile Measurement	Measuring Range	X	0~200mm
		Z	0~500mm
		Z1	±6mm (Optional: ±12mm)
	Resolution		0.001um
	Accuracy	Z1*1	≤± (0.5+0.03 H) μm (H, mm)
		Pt*2	Pt≤0.2μm
		Standard Ball *3	≤±(1+R/20) μm (R, mm)
		Angle*4	≤± 1'
	Moving Speed	X	0~20mm/s
		Z	0~20mm/s
	Scanning Speed		0.05~5mm/s
	X Straightness*5		≤0.25μm/200mm
Measuring Force		0.5mN, 0.75mN, 1mN, 2mN, 3mN(Adjustable)	
Roughness Measurement	Ra Masurement Range		Ra0.012μm~Ra12.5μm
	Accuracy*6		Ra0.012μm ~ Ra3.2 μm: ≤±(3nm+2.0%A),A(Ra)μm Ra3.201μm ~ Ra12.5μm : ≤±(3nm+3.5%A),A(Ra)μm
	Repeatability (1δ)*7		1δ≤1nm
	Measurement Residual*8		Rq≤3nm
	Roughness Parameters		R Roughness : Rp,Rv,Rz,Rc,Rt,Ra,Rq,Rsk,Rku,RSm,RPc,Rdq,Rdc,Rmr,Rmax,Rpm, tp,Htp,Pc,Rda,Ry,Sm,S,Rpc,RzJ; Key Roughness : Rk,Rpk,Rvk,Rpkx,Rvkx,Mr1,Mr2,A1,A2,Vo ; Profile : Pa,Pq,Pt,Pz,Pp,Pv,PSm,Psk,Pku,Pdq,Pdc,Pc,PPc,Pmr,Rad,PzJ,Pmax ; Waviness of Profile : Wa,Wq,Wt,Wz,Wp,Wv,WSm,Wsk,Wku,Wdq,Wdc,Wmr,Wpc,Wc Motif : R,AR,W,AW,Rx,Wx,Wte ; Standards : GB/T 3505-2009,ISO 4287:1997,ISO13565-2:1996,ASME B46.1-2002, DIN EN ISO 4287:2010,JIS B 0601:2013,JIS B 0601-1994, JIS B 0601-1982,ISO 1302:2002
	Aspheric Masurement Parameters		Micro profile parameters: Pt, Pa, Fig;Inclination parameters: Smx , Smn ; Horizontal axis angle parameter: Tilt; Distance parameters between the optical axis and the contour: Xp , Xv , Xt ; Root mean square roughness parameter: RMS; Slope parameters: Slpe mx , Slpemx (x), Slperms; Vertex radius error parameter: Radius Err
	Filter		Gaussian filter, 2RC filter, zero phase filter
	Sampling Length		0.008, 0.08, 0.25, 0.8, 2.5, 8.0 or 25mm Selectable
	Evaluation Length		Auto calculation
Size(L×W×H)			800×500×1080(mm)
Weight			265kg

*1 The accuracy is based on the measurement standard gauge block.

*2 The accuracy is based on the Pt test of standard ball smaller than diameter 25mm.

*3 The accuracy is based on the verification of the Φ 50mm standard ball with the arc exceeds 90 degrees.

*4 The accuracy is based on the measurement of the angle of polygonal prism.

*5 The accuracy is based on the measurement of optical flat.


*6 The accuracy is based on the measurement of standard roughness block.

*7 The repeatability is based on the measurement of 0.1-0.2μm square wave roughness block and standard step height block.

*8 The accuracy is based on the measurement of 1nm level roughness block and optical flat.

Profilometer SJ5730

Once Scanning for both Profile and Roughness



SJ5730-100

SJ5730-200

Functions

Parameter classification		Parameters
Roughness Measurement	Contour Evaluation	P(Original profile), R(Surface roughness profile), W(Waviness)
	Roughness Evaluation	Ra, Rp, Rv, Rz, Rt, Rmax, Rq, Rsk, Rku, RSm, RPc, Rdq, Rdc, Rmr, Motif parameters, RCore parameters, P parameters, W parameters
	Filter	2RC filtering, Gaussian filtering and Zero phase filtering
	Cut-off Wavelength λ_s	0.008, 0.025, 0.08, 0.25, 0.8, 2.5, 8mm selectable
	λ_s	0.25, 0.8, 2.5, 8, 25um selectable, comply with the specifications of JJF 1099-2018, ISO 4288-1996, GBT 1031-2009
	Shape Error	Aspheric surface shape error measurement, linear shape error measurement, arc surface shape error measurement
	Standard	DIN EN ISO 4287:2010, ASME B46.1-2002, JIS B 0601:2013, GB/T 3505-2009, ISO 4287:1997, ISO 13565-2:1996, ISO 1302:2002
Profile Measurement	Common tools	Provides 76 tools, including coordinate creation, construction tools, auxiliary tools, annotations, and geometric tolerances
	CNC Function	Provide CNC measurement mode for batch measurement
	Custom Meas.	Customize the measurement process according to the characteristics of the workpiece (such as surface with hole in the center), avoids the unnecessary measurement area and perform discontinuous measurement.
	Special Tools	Ball screw measurement (corrected helix angle), thread measurement, stage height, groove depth, groove width, area, convexity etc

Application




Pt & Ra of bearing raceway



Ra of gear tooth surface




Ra of engine blade



Ra & Profile of mold



Profile & Roughness of car parts



Profile & Roughness of workpiece

Features

1. Evaluate profile and roughness parameters at the same time after once scanning
2. High precision, high stability, and high repeatability
3. Intelligent management and advanced software analysis system
4. Intelligent protection system during scanning
5. Flexible manual control
6. Nano-scale large roughness measuring range
7. Plug-in probe, easy to replace probe
8. Extremely small measuring force to avoid scratching the surface

Parameters

Model No.			SJ5730-100
Profile Measurement	Measuring Range	X	0~100mm
		Z	0~300mm
		Z1	±6mm (Optional: ±12mm)
	Resolution		0.001um
	Accuracy	Z1*1	≤± (0.5+0.03 H) μm (H, mm)
		Pt*2	Pt≤0.2μm
		Standard Ball*3	≤±1μm(R≤10mm) ; ≤±(0.17+R/12) μm (10<R≤200mm)
		Angle*4	≤±1'
	Moving Speed	X	0~20mm/s
		Z	0~20mm/s
	Scanning Speed		0.05~5mm/s
	X Straightness*5		≤0.2μm/100mm
Measuring Force		0.5mN,0.75mN,1mN,2mN,3mN(Adjustable)	
Roughness Measurement	Ra Masurement Range		Ra0.012μm~Ra12.5μm
	Accuracy*6		Ra0.012μm ~ Ra3.2 μm: ≤±(3nm+2.0%A),A(Ra)μm Ra3.201μm ~ Ra12.5μm : ≤±(3nm+3.5%A),A(Ra)μm
	Repeatability (1δ)*7		1δ≤1nm
	Measurement Residual*8		Rq≤3nm
	Roughness Parameters		R Roughness : Rp,Rv,Rz,Rc,Rt,Ra,Rq,Rsk,Rku,RSm,RPc,Rdq,Rdc,Rmr,Rmax,Rpm, tp,Htp,Pc,Rda,Ry,Sm,S,Rpc,RzJ; Key Roughness : Rk,Rpk,Rvk,Rpkx,Rvkx,Mr1,Mr2,A1,A2,Vo; Profile : Pa,Pq,Pt,Pz,Pp,Pv,PSm,Psk,Pku,Pdq,Pdc,Pc,PPc,Pmr,Rad,PzJ,Pmax; Waviness of Profile : Wa,Wq,Wt,Wz,Wp,Wv,WSm,Wsk,Wku,Wdq,Wdc,Wmr,Wpc,Wc; Motif : R,AR,W,AW,Rx,Wx,Wte; Standards: GB/T 3505-2009,ISO 4287:1997,ISO13565-2:1996,ASME B46.1-2002, DIN EN ISO 4287:2010,JIS B 0601:2013,JIS B 0601-1994, JIS B 0601-1982,ISO 1302:2002
	Aspheric Masurement Parameters		Micro profile parameters: Pt, Pa, Fig; Inclination parameters: Smx , Smn ; Horizontal axis angle parameter: Tilt; Distance parameters between the optical axis and the contour: Xp , Xv , Xt ; Root mean square roughness parameter: RMS; Slope parameters: Slpe mx , Slpemx (x), Slperms; Vertex radius error parameter: Radius Err
	Filter		Gaussian filter, 2RC filter, zero phase filter
	Sampling Length		0.008, 0.08, 0.25, 0.8, 2.5, 8.0 or 25mm Selectable
	Evaluation Length		Auto calculation
	Size(L×W×H)		
Weight			110kg

*1 The accuracy is based on the measurement standard gauge block.

*2 The accuracy is based on the Pt test of standard ball smaller than diameter 25mm.

*3 The accuracy is based on the verification of the Φ 50mm standard ball with the arc exceeds 90 degrees.

*4 The accuracy is based on the measurement of the angle of polygonal prism.

*5 The accuracy is based on the measurement of optical flat.

*6 The accuracy is based on the measurement of standard roughness block.

*7 The repeatability is based on the measurement of 0.1-0.2μm square wave roughness block and standard step height block.

*8 The accuracy is based on the measurement of 1nm level roughness block and optical flat.

Parameters

Model No.			SJ5730-200
Profile Measurement	Measuring Range	X	0~200mm
		Z	0~500mm
		Z1	±6mm (Optional: ±12mm)
	Resolution		0.001um
	Accuracy	Z1*1	≤± (0.5+0.03 H) μm (H, mm)
		Pt*2	Pt≤0.2μm
		Standard Ball *3	≤± 1μm(R≤10mm); ≤±(0.17+R/12) μm (10<R≤200mm)
		Angle*4	≤± 1'
	Moving Speed	X	0~20mm/s
		Z	0~20mm/s
	Scanning Speed		0.05~5mm/s
	X Straightness*5		≤0.35μm/200mm
Measuring Force		0.5mN,0.75mN,1mN,2mN,3mN(Adjustable)	
Roughness Measurement	Ra Masurement Range		Ra0.012μm~Ra12.5μm
	Accuracy*6		Ra0.012μm ~ Ra3.2 μm: ≤±(3nm+2.0%A),A(Ra)μm Ra3.201μm ~ Ra12.5μm : ≤±(3nm+3.5%A),A(Ra)μm
	Repeatability (1δ)*7		1δ≤1nm
	Measurement Residual*8		Rq≤3nm
	Roughness Parameters		R Roughness : Rp,Rv,Rz,Rc,Rt,Ra,Rq,Rsk,Rku,RSm,RPc,Rdq,Rdc,Rmr,Rmax,Rpm, tp,Htp,Pc,Rda,Ry,Sm,S,Rpc,RzJ; Key Roughness : Rk,Rpk,Rvk,Rpkx,Rvkx,Mr1,Mr2,A1,A2,Vo; Profile : Pa,Pq,Pt,Pz,Pp,Pv,PSm,Psk,Pku,Pdq,Pdc,Pc,PPc,Pmr,Rad,PzJ,Pmax; Waviness of Profile : Wa,Wq,Wt,Wz,Wp,Wv,WSm,Wsk,Wku,Wdq,Wdc,Wmr,Wpc,Wc; Motif : R,AR,W,AW,Rx,Wx,Wte; Standards : GB/T 3505-2009,ISO 4287:1997,ISO13565-2:1996,ASME B46.1-2002, DIN EN ISO 4287:2010,JIS B 0601:2013,JIS B 0601-1994, JIS B 0601-1982,ISO 1302:2002
	Aspheric Masurement Parameters		Micro profile parameters: Pt, Pa, Fig; Inclination parameters: Smx , Smn ; Horizontal axis angle parameter: Tilt; Distance parameters between the optical axis and the contour: Xp , Xv , Xt ; Root mean square roughness parameter: RMS; Slope parameters: Slpe mx , Slpemx (x), Slperms; Vertex radius error parameter: Radius Err
	Filter		Gaussian filter, 2RC filter, zero phase filter
	Sampling Length		0.008, 0.08, 0.25, 0.8, 2.5, 8.0 or 25mm Selectable
	Evaluation Length		Auto calculation
	Size(L×W×H)		
Weight			180kg

*1 The accuracy is based on the measurement standard gauge block.

*2 The accuracy is based on the Pt test of standard ball smaller than diameter 25mm.

*3 The accuracy is based on the verification of the Φ 50mm standard ball with the arc exceeds 90 degrees.

*4 The accuracy is based on the measurement of the angle of polygonal prism.

*5 The accuracy is based on the measurement of optical flat.

*6 The accuracy is based on the measurement of standard roughness block.

*7 The repeatability is based on the measurement of 0.1-0.2μm square wave roughness block and standard step height block.

*8 The accuracy is based on the measurement of 1nm level roughness block and optical flat.

Profilometer SJ5760 Series

Independent Profile and Roughness Measurement Module



Application



Bearing



Railway part



Thread workpiece



Car parts



Ballscrew



Stamping part



Thread workpiece



Gear




Machining part



Roughness specimen



Plastic part



Engine cylinder



Custom bearing



Mold

































Die casting



Software

Surf & Rough X is an user-friendly and powerful software, which is completely developed by Chotest. It can analyze not only surface contour, but also evaluate surface roughness. Surf&Rough X contains 76 kinds of utility tools, such as coordinate system, construction tools, geometric tolerance, surface roughness assessment tools, etc. CNC measurement mode is a convenient function for batch measurement, and it improves measurement efficiency greatly. Moreover, discontinuous measurement function is also available for the special workpieces.

Functions

		GD & T	Straightness, roundness, position degree, parallelism, perpendicularity, contour degree, etc.
		Custom Program	The measurement process can be customized according to the characteristics of the workpiece (Set the probe to jump deep holes, steep slopes or obstacles).
		CNC Mode	The one-key measurement program can be built for batch measurement. If the tolerance is also entered to the program, the measurement result will be automatically judged as OK or NG.
		Coordinate system	Coordinate system could be established by point-line or line-line, and it could be translated and rotated.
		Special Tool	Ball screw shaft measurement(corrected helix angle),thread measurement, step height, groove depth, groove width, area, curvature, etc.
		Report	Export report in .doc, .xls or .pdf, and support user-defined report template.
		Contour Comparison	After import CAD drawing to the software, the user can compare the difference between drawing and scanning contour.
		Roughness	Ra, Rp, Rv, Rz, Rt, Rmax, Rq, Rsk, Rku, RSm, R _{Pc} , Rdq, Rdc, Rmr, Pa, Pq, Pt, Pp, Pv, Psm, Psk, Pku, Pdq, Plq, Pdc, PHSC, Ppc, PMr, Waviness of Profile, Motif, etc.
			
			
			
			
			
			
			

Profile Example



Software

Scanning Settings:

Set measuring conditions, Inspection info and scanning positions.

Tool bar:


Extraction tools and Annotation tools.

Switch meas. function:

Switch between profile measurement and roughness measurement

Scanning graph window:

Display the scanning graph and perform the analysis operation.



Motion control:

Control probe to move \uparrow , \downarrow , \leftarrow , \rightarrow , and stop, reset.

Coordinate display:

Display the coordinates of current probe position.


Status Bar:

Network, serial port, unit, operation tips, login time, user name, etc.


Analysis data:

List features, measured data and tolerance.

Measurement Interface



Profile measurement




Roughness measurement

Parameters

Model No.		SJ5760-PR
Travel Range	X	0~200mm
	Z	0~450mm
Size(L×W×H)		800×450×1100mm
Weight		220Kg
Profile Measurement(SJ5760-P)		
Measuring Range	Z1	±25mm
	Resolution	0.001um
Indication Error	X	±(0.6+0.015L)μm(L, mm)
	Z1	±(0.6+0.05H)μm(H, mm)
	Standard Ball	±(1+R/15)μm(R, mm)
	Angle error	≤±1'
Moving speed	X	0~20mm/s
	Z	0~20mm/s
Scanning Speed		0.05~5mm/s
Max Slope		Uphill 77°, downhill 88°
Straightness		≤1μm/200mm
Scanning Force		10~150mN adjustable
Roughness Measurement(SJ5760-R)		
Measuring Range	Z0	±400μm(Optional:±1000μm)
	Sensor Type	Railless
	Ra Range	Ra0.1μm~Ra64μm
Scanning Force		1mN
Resolution	Z0	0.001um
Indication Error		±(5nm+2.5%A)μm, A(Ra)μm
Repeatability		≤1nm
Scanning Speed		0.05~0.5mm/s
Measurement Residual		≤0.005μm
Roughness Parameters		R Roughness: Rp,Rv,Rz,Rc,Rt,Ra,Rq,Rsk,Rku,RSm,RPc,Rdq, Rdc,Rmr, Rmax, Rpm,tp,Htp,Pc,Rda,Ry,Sm,S,Rpc,RzJ; Key roughness: Rcore: Rk,Rpk,Rvk,Rpkx,Rvkx,Mr1,Mr2,A1,A2,Vo; Profile: Pa,Pq,Pt,Pz,Pp,Pv,PSm,Psk,Pku,Pdq,Pdc,Pc,PPc,Pmr,Rad,PzJ,Pmax; Waviness of Profile: Wa,Wq,Wt,Wz,Wp,Wv,WSm,Wsk,Wku,Wdq,Wdc, Wmr,Wpc,Wc; Motif: R,AR,W,AW,Rx,Wx,Wte;
Filter		2RC filtering, Gaussian filtering and Zero phase filtering
Sampling Length		0.008, 0.08, 0.25, 0.8, 2.5, 8.0 or 25mm Selectable
Evaluation Length		Auto calculation
Film Thickness Measurement	Measuring Range	60μm or less
	Measuring Accuracy	2%H(H is measuring height in μm)

SJ5718 Series Economic Profilometers



Application



Mechanical part



Metallurgy part



Car wheel



Die casting part



Bearing



Thread part



Battery housing



Phone housing



Machining part



Gearbox pulley

Parameters

Model No.		SJ5718-PR
Travel Range	X	0~100mm
	Z	0~300mm
Size(L×W×H)		600×350×890mm
Weight		115Kg
Profile Measurement(SJ5718-P)		
Measuring Range	Z1	±30mm
	Resolution	0.001um
Indication Error	X	±(0.6+0.02L)μm(L,mm)
	Z1	±(0.6+0.05H)μm(H,mm)
	Standard Ball	≤±(1.2+R/15)μm(R,mm)
	Angle error	≤±1'
Moving speed	X	0~20mm/s
	Z	0~20mm/s
Scanning Speed		0.05~5mm/s
Max Slope		Uphill 77°, downhill 88°
Straightness		≤0.5μm/100mm
Scanning Force		30mN adjustable
Roughness Measurement(SJ5718-R)		
Measuring Range	Z0	±400μm(Optional:±1000μm)
	Sensor Type	Railless
	Ra Range	Ra0.1μm~Ra64μm
Scanning Force		1mN
Resolution	Z0	0.001um
Indication Error		≤±(5nm+2.5%A)μm, A(Ra)μm
Repeatability		≤1nm
Scanning Speed		0.05~0.5mm/s
Measurement Residual		≤0.005μm
Roughness Parameters		R Roughness: Rp,Rv,Rz,Rc,Rt,Ra,Rq,Rsk,Rku,RSm,RPc,Rdq, Rdc,Rmr, Rmax, Rpm,tp,Htp,Pc,Rda,Ry,Sm,S,Rpc,RzJ; Key roughness: Rcore: Rk,Rpk,Rvk,Rpkx,Rvkx,Mr1,Mr2,A1,A2,Vo; Profile: Pa,Pq,Pt,Pz,Pp,Pv,PSm,PsK,Pku,Pdq,Pdc,Pc,PPc,Pmr,Rad,PzJ,Pmax; Waviness of Profile: Wa,Wq,Wt,Wz,Wp,Wv,WSm,Wsk,Wku,Wdq,Wdc, Wmr,Wpc,Wc; Motif: R,AR,W,AW,Rx,Wx,Wte;
Filter		2RC filtering, Gaussian filtering and Zero phase filtering
Sampling Length		0.008, 0.08, 0.25, 0.8, 2.5, 8.0 or 25mm Selectable
Evaluation Length		Auto calculation
Film Thickness Measurement	Measuring Range	60μm or less
	Measuring Accuracy	2%H(H is measuring height in μm)

Stylus Nano Profiler CP200

Surface micro-nano profile measurements





- Powerful data collection and analysis system
- Excellent repeatability and reproducibility



Description

Stylus Nano Profiler CP200 is an ultra-precision contact measuring instrument for measurement of surface roughness and microscopic profile, such as micro-nano step height, film thickness. The CP200 uses a displacement sensor with sub-angstrom resolution, ultra-low noise signal acquisition, ultra-fine motion control, and calibration algorithms technology with excellent performance. Its contact force is extremely small, and there are no special requirements for measuring surface reflection characteristics, material types, and material hardness, consequently, it is widely used to measure microscopic surface for industries of semiconductors and compound semiconductors, high-brightness LEDs, solar energy, MEMS micro-electromechanical systems, touch screens, automotive and medical equipment.

Application

			
Semiconductor	Large Substrate	Glass substrate and display	Film on flexible component
<ul style="list-style-type: none"> • Step height of deposited film • Step height of thin Film Resist • Etch rate measurement • Chemico-mechanical polishing (corrosion, pitting, bending) 	<ul style="list-style-type: none"> • PCB protrusion, step height • Window coating • Wafer mask • Wafer chuck coating • polishing plate 	<ul style="list-style-type: none"> • AMOLED • Step height measurement during LCD screen development • Thickness measurement for touch panel film Solar Coating Thin Film Measurements 	<ul style="list-style-type: none"> • Organic photodetector • Organic films printed on film and glass Touch screen copper traces

Parameters

Model No.	CP200	
Measurement technology	Stylus Scanning	
Navigation Camera	5M pixels colorful camera, FOV 2200×1700μm	
Sensor	Ultra Low Inertia, LVDC Sensor	
Measuring Force	1-50mg Adjustable	
Stylus	Tip radius 2μm , angle 60°	
Object	XY Travel Range	150mm×150mm, Motorized
Table	Rotation	0~360°, Motorized
Max Scanning Length	55mm	
Max Sample Height	50mm	
Max Wafer Size	150mm(6"), 200mm(8")	
Step Height Repeatability	5 Å @ Range 330μm/ 10 Å @ Range 1mm (Measure step height 1μm, 1δ)	
Sensor Range*1	330μm or 1mm	
Vertical Resolution	Resolution<0.01 Å(When the grade is 13μm)	
Scanning Speed	2μm/s~10mm/s	
Size(L×W×H)	640×626×534mm	
Weight	40kg	
Input	AC100~240 V, 50/60 Hz, 200W	
Working environment	Humidity: 30~40% RH(No condensation), Temp.: 16~25°C(Fluctuation < 2°C/h), Audio noise: ≤80dB Ground vibration: 6.35μm /s(1~ 100Hz), Air laminar flow: ≤ 0.508 m/s(Downward flow)	

*1 The sensor range can only be selected either 330μm or 1mm

Machine Tool Probes PO Series

Precision, Reliable



PO60



PO40




PO40L

PO series contains 3-point trigger unit inside the probe, which is the most stable structure. When the stylus is moved radially or axially by external force, the trigger unit is triggered. Then the circuit inside of probe sends a triggering signal to the receiver, and the receiver transmits it to the machine tool, consequently the present coordinates of each axis of the machine tool are recorded automatically. Finally measurement results are calculated according to the coordinate records of related

Features

- High repeatability: One-way repeatability $<1\mu\text{m}$
- Long standby time: As long as 6 months
- Omnidirectional energy-absorbing design: 360° omnidirectional energy-absorbing design, which helps to cushion the spindle in impact when an operating accident occurs
- Waterproof design: IP68 for probe and receiver
- Intelligent LED indicators: Show current working status of the probe



Parameters

1) Storage temperature: (-25~70)°C

2) Working temperature: (5~55)°C

Model No.	PO40	PO60	PO40L
Size	Φ40mm×L50mm	Φ63mm×L76mm	Φ40mm×L52mm
Weight(Without Holder)	260g	880g	280g
Transmission Type	360° IR	360° IR	360° IR
Transmission Distance	5m	6m	5m
Starting Mode	Code M	Code M, Revolve	Code M
Rotational Speed	Max 1000rev/min	Max 1000rev/min	Max 1000rev/min
Power Supply	1/2AA 3.6V battery×2	AA1.5V/3.6V battery×2	1/2AA 3.6V battery×2
Triggering Direction	±X/±Y/-Z	±X/±Y/-Z	±X/±Y/-Z
Repeatability of One-way triggering 2σ ^{*1}	1μm	2μm	1μm
Max overrun ^{*2}	XY:12.5mm +Z:6mm	XY:21mm +Z:11mm	XY:12mm +Z:6mm
XY Trigger Force ^{*3}	0.5N~ 0.9N	0.5N~1.6N Adjustable	0.3N~1.6N Adjustable
Z Trigger Force	5.8N	3.5N~14N Adjustable	4N~10N Adjustable
Application	Small and mediumsized 3-axis, 5-axis machining center	Large gantry machine tool, horizontal machining center	CNC lathe or turning-milling composite machining center

Note: .

* 1: Test with a 50mm straight stylus under speed 480mm/min

* 2: Test with a 50mm straight stylus

* 3: Test with a 50mm straight stylus under speed 480mm/min

Parameters of Receiver

1) Transmission type: IR, 360°

2) Working range: Max 8m

3) Weight: 926g

4) Input voltage: 12V~ 30V

5) Input current: <100mA, receiving <40mA

6) Cable to machine controller: dedicated 13PIN shielded cable,
8 meters or 15 meters


7) Storage temperature: (-25~70)°C, working temperature: (5~55)°C




COMI Receiver



Professional Inspection Equipment



WD4000 Series Unpatterned Wafer 3D Inspection System





Description

Unpatterned Wafer 3D Inspection System WD4000 series can automatically measure wafer thickness, surface roughness, and micro-nano 3D microtopography at a time. Use white light confocal probes to measure wafer thickness, TTV, LTV, BOW, WARP, line roughness; use white light interferometry probe to scan the Wafer surface to create a 3D profile image of the surface , then analyze the roughness and relevant 2D and 3D parameters according to ISO/ASME/EUR/GBT standards.

Application

Thickness and warpage measurement for unpatterned wafer




Measurement results of wafer thickness and warpage


The 3D shape based on the upper and lower surfaces of the wafer is reconstructed by non-contact measurement. The powerful measurement and analysis software ensures the stable calculation for the thickness, roughness, total thickness variation(TTV) of the wafer.

Application


Roughness measurement for unpatterned wafer




Thinned silicon wafer



3D image of
rough grinding silicon wafer



3D image of
fine grinding silicon wafer



Sa curve of 25 times measurement data for fine grinding wafer

文件	3D参数分析					
序号	名称	图标	Sq[高度参数][L]	Sp[高度参数][L]	Sv[高度参数][L]	Sz[高度参数][L]
1	sa_1		7.597	25.179	318.103	344.283
2	sa_2		8.286	24.884	318.429	344.113
3	sa_3		7.092	24.394	318.239	340.693
4	sa_4		6.772	25.329	320.329	345.694
5	sa_5		6.990	24.388	318.774	343.162
6	sa_6		7.330	24.584	318.127	340.280
7	sa_7		9.190	24.424	308.328	332.754
8	sa_8		8.700	24.930	319.030	343.961
9	sa_9		7.583	25.466	313.352	338.818
10	sa_10		9.636	24.834	318.285	343.119
11	sa_11		7.269	25.343	318.515	343.858
12	sa_12		7.148	25.536	318.074	343.630
13	sa_13		7.425	24.911	318.300	343.211
14	sa_14		7.461	25.519	318.559	344.078
15	sa_15		7.340	24.968	318.259	342.927
16	sa_16		6.986	24.710	312.806	337.538
17	sa_17		9.301	24.792	313.648	338.350
18	sa_18		7.826	25.271	314.494	339.760
19	sa_19		7.294	24.903	311.570	338.472
20	sa_20		7.084	24.940	318.023	341.563
21	sa_21		7.260	25.017	318.442	335.479
22	sa_22		7.757	25.130	315.120	340.250
23	sa_23		8.493	24.773	316.354	341.127
24	sa_24		7.373	24.986	318.743	341.729
25	sa_25		7.545	25.111	316.822	341.653
统计	平均		7.734	24.935	318.292	341.227

Multi-file analysis of 25 times measurement data for fine grinding wafer

During rough grinding and fine grinding process for the Wafer thinning, the surface roughness Sa values and their stability are used to evaluate the processing quality. When the thinned silicon wafer is measured in the strong noise environment of the production workshop, the roughness Sa values of the fine grinding silicon wafers are ranging around 5nm, and the repeatability is 0.046987nm based on 25 times of measurement data which proves the measurement stability is good.

Parameters

Model No.		WD4100	WD4200
Wafer Size		2", 4", 6", 8", 12"	
Wafer Table		Vacuum chuck	
Loading and Unloading		Manual(Auto robot arm is optional)	
XYZ Travel range		400mm/400mm/75mm	
Max Moving speed		500mm/s	
Main Frame		Marble	
Anti-Vibration		Air-floating anti-vibration system	
Loading capacity		≤5kg	
Overall Size		2047×1543×2000mm	
Weight		About 2000kg	
Compressed Air		0.6MPa; 60L/min	
Working Environment		Temp. 20°C±1°C/hour, RH 30~80%	
Ambient Vibration		< 0.002g, less than 10Hz	
Thickness Measurement System			
Material of Object		Arsenide, nitride, phosphorus, germanium, phosphorurate, lithium crickets, sapphire, silicon, silicon carbide, glass, etc.	
Sensor		High-precision white light confocal sensors	
Measuring range		10μm~2000μm	
Scanning Path		Full map area scanning, Union Jack path, free multi-point	
Accuracy		±0.25μm	
Repeatability(σ)		0.2μm	
Resolution		17nm	
Measurement Parameters		Thickness, TTV (Total thickness variation), LTV, BOW, warp, flatness, line roughness	
3D microtopography Measurement System			
Measurement Principle		——	White light interferometry
Light Source		——	White LED
Objective Lens		——	10X(2.5X, 5X, 20X, 50X are optional)
Field of View		——	0.96 mm×0.96 mm
Lens Turret		——	Manual 3 holes turret (Motorized 5 holes turret is optional)
Level Adjustment		——	±2°
Z-axis Scanning Range		——	10 mm
Z-axis Resolution		——	EVSI:0.5nm;EPSI:0.1nm
Lateral Resolution		——	0.5~3.7μm
Scanning Speed		——	2.5~5.0μm/s
Characters of Test Object		——	Reflectivity 0.05%~100%
Roughness RMS Repeatability* ¹		——	0.005nm
Step Height Measurement* ²	Accuracy	——	0.3%
	Repeatability	——	0.08%1σ
Measurement Parameters		——	Microtopography, line/surface roughness, spatial frequency, etc.

*1 Roughness performance is obtained by measuring SQ parameters for a 0.2nm SA silicon wafer in the laboratory environment according to ISO 25178.

*2 Step height performance is obtained by measuring a standard 4.7μm stage block in the laboratory environment according to ISO 5436-1: 2000.

Patterned Wafer Critical Dimension & Overlay Measurement System BOKI_1000




Description

Patterned Wafer Critical Dimension & Overlay Measurement System is an optical inspection instrument that can perform both high-precision XY plane dimension inspection and sub-nanometer surface 3D topography measurement. It can scan multiple regions on a large surface accurately and automatically with excellent repeatability, which significantly increases the measurement efficiency and reduces human error.

Equipping high-resolution optical lens, combining high-precision image analysis algorithm, in CNC mode the system can automatically position & recognize the measuring objects, then automatically measure and evaluate all sizes according to program. At the same time, it integrates white light interferometry measurement system, which can scan the wafer surface to create a 3D profile image of the surface, then analyze Z-direction sizes in nanometer level.


It is widely used in ultra-precision machining industries such as semiconductor manufacturing and packaging process inspection, optical processing, MEMS components, etc.

Application





Overlay Offset Measurement

During wafer manufacturing, the offset of the overlay after photoetching process is measured in Photo area, exposure of wafer, and compensation values based on the measurement are imported into the lithography machine to optimize the stability of the wafer photoetching process.





Key Dimensions Measurement

During wafer manufacturing, it requires to control critical dimensions of Die in multiple processes, and SuperView automatically extracts the feature edges of Die, and at the same time it measures all features according to program efficiently and accurately.





3D Dimensions Measurement

During wafer manufacturing, it is necessary to measure the bottom width of the grooves to check whether the distance between dies is qualified after the previous process in Photo area. The software automatically select multiple parabolas to obtain average value for target positions after auto scanning, then the parameters of the exposure machine is adjusted based on the measurement result in order to meet the process requirements.



Etch Depth Measurement and Profile Analysis

Reconstruct the 3D image of the wafer, and extract the cross-sectional profile of the groove lines for analysis, then evaluate the integrity of the grooves profile and observe the defect at the bottom of grooves.



Laser Groove Depth and Width Measurement

After the laser engraving process, laser U-groove depth and width should be measured. The software can customize the width of the lasso to extract mean value profile curve of the groove, then calculate the average depth & width values of the groove. The parameters of the laser machine is adjusted to meet the process requirements based on measurement results.

Parameters

Model No.	BOKI_1000	
Loading Bin	4 pcs of Cassette, size is customizable	
Feeding Sensor	With anti-skid function	
Light Source	White/Green LED (single or double is optional)	
Barcode Scanner	Barcode recognition	
Barcode Scanner	1024X1024	
Micro Objective Lens	10×, 20×, 50×	
Measurement Accurac	10X:±0.5μm; 20X:±0.4μm; 50X:±0.3μm	
Repeatability(σ)* ¹	10X:±0.2μm; 20X:±0.2μm; 50X:±0.1μm	
Interferometric Objective Lens	2.5×, 5×, 10×, 20×, 50×, 100×	
Z axis Resolution	0.1nm	
Lateral Resolution (0.5λ/NA)	100X~2.5X: 0.5μm~3.7μm	
Roughness RMS Repeatability* ²	0.005nm	
Surface Profile Repeatability	0.1nm	
Step Height Measurement* ³	Repeatability	Accuracy
	0.1% 1σ	0.75%
Software	SuperView	
Field of View	0.49×0.49mm (@Optical Zoom 0.75×)	
Max Field of View	6×6mm	
Lens Turret	Manual 3 holes turret(Optional: Motorized 5 holes turret)	
Object Table	XY Travel Range	300×300mm
	Load Capacity	5kg
	Flatness	< 10μm
	Control Mode	Motorized
Z-Axis	Travel Range	30mm
	Control Mode	Motorized
Vacuum Chuck(Optional)	Negative pressure ≤-80KPa	
Overall Dimension(L×W×H)	1800×1400×1710mm	
Dustproof Device FFU	Class 1000	
Required Dust-Free Environment Level	Class 1000	
Oil-Proof Device	All guide rails must be provided with oil shields, and oil stains and other substances cannot fall out.	
Equipment Weight	800KG	
Power Supply	AC 220V,50/60HZ, 13~14A,3000W	
Compressed Air	1.Air-floating anti-vibration system: Max flow 1.5LPM; Average flow 1LPM; Pressure 0.6MPa; Hose diameter 6mm; 2.Vacuum chuck: Max flow 250LPM; Average flow 180LPM; Pressure ≤ -80kpa; Hose diameter 8mm;	
Working Environment	Temp.: 15~30°C, humidity : 30~80% (no condensation)	
Safety	The equipment has door magnetic interlocking function, and the automatic door is equipped with safety grating.	

*1 Accuracy and repeatability are obtained by measuring Standard Resolution Test Board.

*2 Roughness Performance is obtained by measuring SQ parameters of a Sa 0.2nm silicon wafer in the laboratory environment according to ISO 25178.

*3 Step height performance is obtained by measuring a standard 4.7μm stage block in the laboratory environment according to ISO 5436-1: 2000.



Dimensional Calibrators



SJ5100 Series

Universal Length Measuring Machine

Absolute measurement over entire measuring range



Functions

1. Measure gauge blocks, thread gauges, plain gauges, Taper thread/plain gauges, pin gauge, caliper, spline gauges, setting bars, snap gauges, internal/external micrometers, feeler gauges, Dial indicators, dial bore gauge, dial test gauges, internal micrometer three points, etc.
2. Measure various gauges according to GB, ISO, BS, ANSI, DIN, JIS, API standards. With comprehensive and professional standards in database, it meets requirements of most customers.
3. Conform to a variety of verification regulations & measuring standards. All test results are generated according to relevant regulations and standards.
4. User-friendly software.
5. With centralized database management for measuring records, the operator can query and manage the measuring records according to object type, testing institution, manufacturing number, inspector, submitted institution, equipment number, inspection date and effective date.
6. Support to print multiple selected test records or test certificates from database at once time.
7. Support to export test data to Word, Excel, AutoCAD (optional) files.
8. Data backup and restore.
9. Support user-defined template of report.
10. Support user-defined standard/tolerance.

Application



Big plain ring gauge



Spline plug gauge



Spline ring gauge



Taper thread ring gauge



Thread ring gauge



Snap gauge



Caliper



Micrometer 3 points



External micrometer



Setting bar



Small plain ring gauge



Internal micrometer




Long gauge block



Pin gauge



Inner ring of bearing



Taper thread plug gauge



Dial test gauge



Depth micrometer



Digital radius gauge



Carbon fiber comparison gauge

Main Accessories



Workholder for taper gauge



Workholder for gauge block



Workholder for micrometer



One-coordinate floating table



V-shaped block



Five-axis object table



Workholder for micrometer 3 points



Measuring jaw



Inside measuring device



Ruby probes



Plain/Blade anvil



Spherical anvil & Measuring bar

Software



Parameters

Model No.		SJ5100-UP300	SJ5100-UP600	SJ5100-UP1000
Absolute measurement	External range	0-340mm	0-640mm	0-1040mm
	Internal range	0.7~200mm	0.7~500mm	0.7~900mm
Indication error		$\pm(0.09+L/1500)\mu\text{m}$ (Note: L is measured length in mm)		
Repeatability (2s)		0.06 μm		
Resolution(μm)		0.01 μm		
Max pitch diameter(mm)		200mm(Ring)/250mm(Plug)		
Measuring force		0.05N, 0.1N, 0.3N, 0.5N, (1~10)N continuously adjustable by hand		
Operation environment		20 \pm 0.5 $^{\circ}\text{C}$, fluctuation \leq 0.2 $^{\circ}\text{C}$ /hour, Related Humidity: 20~60%		
Dimension(mm)		1400 \times 400 \times 450	1400 \times 400 \times 450	1700 \times 400 \times 450
Weight(kg)		150kg	150kg	180kg
Five-axis object table	Z-axis range	0~50mm		
	Y-axis range	\pm 25mm		
	X-axis floatation	\pm 10mm		
	Z-axis rotation	\pm 3 $^{\circ}$		
	Y-axis yaw	\pm 3 $^{\circ}$		
	Loading capacity	\leq 50kg		
	Dimension	350mm \times 125mm		

Model No.		SJ5100-300A/B	SJ5100-600A/B	SJ5100-1000A/B	SJ5100-1500A/B	SJ5100-2000A/B	SJ5100-3000A/B
Absolute measurement	External range	0~340mm	0~640mm	0~1040mm	0~1540mm	0~2040mm	0~3040mm
	Internal range	0.7~200mm	0.7~500mm	0.7~900mm	0.7~1400mm	0.7~1900mm	0.7~2900mm
Indication error		A series: $\pm(0.12+L/1000)\mu\text{m}$; B series: $\pm(0.20+L/1000)\mu\text{m}$ (Note: L is measured length in mm)			A series: $\pm(0.25+L/1000)\mu\text{m}$; B series: $\pm(0.4+L/1000)\mu\text{m}$ (Note: L is measured length in mm)		
Repeatability (2s)		A Series:0.08 μm ; B Series 0.10 μm			A Series:0.15 μm ; B Series 0.20 μm		
Resolution(μm)		0.01 μm					
Max pitch diameter(mm)		200 mm(Ring)/250mm(Plug)					
Measuring force		0.05N, 0.1N, 0.3N, 0.5N, (1~10)N continuously adjustable by hand					
Operation environment		A series: 20 \pm 1 $^{\circ}\text{C}$, fluctuation \leq 0.2 $^{\circ}\text{C}$ /hour, Related Humidity: 20~60% B series: 20 \pm 2 $^{\circ}\text{C}$, fluctuation \leq 0.5 $^{\circ}\text{C}$ /hour, Related Humidity: 20~60%					
Dimension(mm)		1400×400×450	1400×400×450	1700×400×450	2200×400×450	2700×400×450	3700×400×450
Weight(kg)		150kg	150kg	180kg	310kg	360kg	410kg
Five-axis object table	Z-axis range	0~50mm					
	Y-axis range	\pm 25mm					
	X-axis floatation	\pm 10mm					
	Z-axis rotation	\pm 3 $^{\circ}$					
	Y-axis yaw	\pm 3 $^{\circ}$					
	Loading capacity	\leq 50kg					
	Dimension	350mm×125mm					

SJ5200/SJ5500 Series Universal Thread Measuring Machines



SJ5200



SJ5500

Functions

1. Full-automatic measurement for comprehensive parameters of cylindrical thread plug gauges, cylindrical thread ring gauges, taper thread plug gauges, taper thread ring gauges, plain ring gauges, plain plug gauges and other gauges with internal & external dimensions, including virtual pitch diameter, single pitch diameter, basic pitch diameter, major diameter, minor diameter, thread pitch, thread angle, half of thread angle, flank straightness, lead angle, taper, etc.
2. Can measure trapezoidal thread gauges, buttress thread gauges, sawtooth thread gauges and other large-slope thread gauges.
3. Can measure comprehensive parameters of single thread and multiple thread.
4. Can measure various thread gauges according to GB, ISO, BS, ANSI, DIN, JIS, API standards. With comprehensive and professional thread standards in database, it meets requirements of most customers.
5. Automatically generate test report according to selected standard.
6. After once measurement, the software can calculate various parameters of thread and display data of any position, it also could generate the thread curve, relevant parameters and analysis chart automatically.
7. Measuring probe and workholder are identified automatically, which avoids collision of measuring probe caused by misoperation.
8. One-sided or two-sided measurement and analysis for gauges.
9. Controller for measuring pin positioning: with an easy-to-use buttons control box, the operation is more flexible.
10. User-friendly software, simple and easy-to-use.
11. Test results are saved automatically with name of measuring series number + size of measuring gauge + type of measuring gauge. With centralized database management for measuring records, the user can query and manage the measuring records according to object type, testing institution, manufacturing number, inspector, submitted institution, equipment number, inspection date, effective date, etc.
12. Can print multiple selected test records or test certificates from database at once time.
13. Can export test data to Word, Excel, AutoCAD (optional) files.
14. Data backup and restore.
15. Can output reports in a variety of formats in Word or PDF, moreover the report format can be customized.
16. Support user-defined standards.

SJ5200 Application



Thread plug gauge



Plain ring gauge



Taper plain ring gauge



Taper plain plug gauge

SJ5200 Parameters

Model No.	SJ5200-60	SJ5200-100	SJ5200-160
External measuring range	(1.0-50)mm	(1.0-90)mm	(1.0-150)mm
Internal measuring range	(2.5-60)mm	(2.5-100)mm	(2.5-160)mm
Max scanning range	60mm(Optional 75mm)	60mm(Optional 75mm)	60mm(Optional 75mm)
Min pitch	0.1mm	0.1mm	0.1mm
Weight	200kg	250kg	300kg
Size	1000×450×1000mm	1000×450×1000mm	1000×450×1130mm

Measurement uncertainty

Cylindrical or Taper thread ring gauge(Minor diameter>2.5mm,half of thread angle≥27°)

Minor diameter(μm)	$2.5 + L/200$	$2.5 + L/200$	$2.5 + L/200$
Actual pitch diameter(μm)	$2.5 + L/200$	$2.5 + L/200$	$2.5 + L/200$
Pitch(μm)	$0.75 + L/200$	$0.75 + L/200$	$0.75 + L/200$

Cylindrical or Taper thread plug gauge(Major diameter>1mm,half of thread

Major diameter(μm)	$2.0 + L/200$	$2.5 + L/200$	$2.5 + L/200$
Actual pitch diameter(μm)	$2.0 + L/200$	$2.5 + L/200$	$2.5 + L/200$
Pitch(μm)	$0.75 + L/200$	$0.75 + L/200$	$0.75 + L/200$

Cylindrical or Taper plain gauge(Diameter from 1mm to 10mm)

Diameter(μm)	$1.5 + L/200$	$2.0 + L/200$	$2.0 + L/200$
--------------	---------------	---------------	---------------


Cylindrical or Taper plain gauge(Diameter>10mm)

Diameter(μm)	$1.0 + L/200$	$1.5 + L/200$	$1.5 + L/200$
--------------	---------------	---------------	---------------

SJ5500 Application



Thread plug gauge



Taper plain plug gauge



API gauge



API gauge

SJ5500 Parameters

Model No.	SJ5500-200	SJ5500-300	SJ5500-400	SJ5500-500	SJ5500-600
External measuring range	(1.0-250)mm	(1.0-350)mm	(1.0-450)mm	(1.0-550)mm	(1.0-620)mm
Internal measuring range	(2.5-250)mm	(2.5-350)mm	(2.5-450)mm	(2.5-550)mm	(2.5-620)mm
Max scanning range	250mm				
Min pitch	0.1mm				
Weight	2000kg				
Size	2000×900×910mm				

Measurement uncertainty

Cylindrical or Taper thread ring gauge(Minor diameter>2.5mm,half of thread angle≥27°)

Minor diameter(μ m)	$3.0 + L/200$
Actual pitch diameter(μ m)	$3.0 + L/200$
Pitch(μ m)	$0.8 + L/200$

Cylindrical or Taper thread plug gauge(Major diameter> 1mm,half of thread

Major diameter(μ m)	$2.9 + L/200$
Actual pitch diameter(μ m)	$2.9 + L/200$
Pitch(μ m)	$0.8 + L/200$

Cylindrical or Taper plain gauge(Diameter from 1mm to 10mm)

Diameter(μ m)	$2.0 + L/200$
--------------------	---------------

Cylindrical or Taper plain gauge(Diameter> 10mm)

Diameter(μ m)	$2.0 + L/200$
--------------------	---------------

SJ2018/2620

Automated Dial Indicator Testing Machines

Precision, Versatile, Efficient



SJ2018



SJ2620

Parameters

Model No.	SJ2018	SJ2620
Measuring range	(0-50)mm	
Resolution	0.01μm	
Repeatability	0.1μm	
Reading accuracy	1/60 of division value for Resolution 0.01mm dial indicator 1/30 of division value for Resolution 0.001mm dial indicator	
Indication error	Random 1mm≤0.6μm Random 2mm≤0.6μm Random 10mm≤0.8μm Random 30mm≤0.9μm 50mm≤1μm	
Hysteresis	≤0.5μm	
Interface	RS232 (Can convert to USB)	
Input voltage	AC100~240V , 50~60Hz	
Operating environment	Temp.(20±2)°C , RH(50~70)%	
Dimension	640×240×530mm	300×235×640mm
Weight	35kg	25kg

Functions

1. Measure dial indicators, micrometer dial indicators, dial test indicators, dial bore indicators, automatically according to the relevant regulations and standards.
2. Measure the above gauges with digital display automatically.
3. Measure the above gauges with imperial system automatically.
4. Support semi-auto testing mode.
5. Automatic zeroing after click "Start".
6. Overtolerance hinting during measuring process.
7. Process and qualify the measured data automatically.
8. Can search and manage the test records according to object type, manufacturer, serial No., inspector, applicant, equipment No., inspection date or effective date etc.
9. Can print or export former test records including error sheet or curve.
10. Can print or export multiple selected test records from database once time.
11. Can export test data in CSV, EXCEL, WORD.
12. Data backup and restore.
13. Can customize format of test report according to requirements of customer.
14. Support user-defined testing program and tolerance.

Application



Digital dial indicator



Dial test indicator



Dial bore indicator




Mechanical comparator

SJ2100

Automated Dial Indicator Testing Machines

Large measuring range (0-100)mm



Parameters

Model No.	SJ 2100
Measuring Range	(0-100)mm
Resolution	0.1μm
Repeatability	0.1μm
Reading Accuracy	1/60 of division value for Resolution 0.01mm dial indicator 1/30 of division value for Resolution 0.001mm dial indicator
Indication Error	Random 1mm≤1μm, Random 2mm≤1μm, Random 10mm≤1.5μm Random 30mm≤2μm, Random 50mm≤2.5μm, 100mm≤4μm
Hysteresis	≤ 0.5μm
Interface	RS232 (Can convert to USB)
Input Voltage	AC100~240V, 50~60Hz
Operating Environment	Temp.(20±2)°C, RH(50~70)%
Dimension	700×250×165mm
Weight	30Kg

Workholder for plunger dial indicator

Item No.: SJ20D, SJ20A

Function: For testing of regular dial indicators

Stem diameter of indicator: $\Phi 8\text{mm}$



Workholder for lever-type indicator and bore dial indicator

Item No.: SJ20B

Function: For testing of dial test indicators and dial bore indicators

Stem diameter of indicator: $\Phi 4$, $\Phi 6$, $\Phi 8\text{mm}$ (dial test indicators); $\Phi 6 \sim \Phi 28\text{mm}$ (dial bore indicators)



Extension bar for camera

Item No.: SJ22

Function: For testing of dial bore indicators with long stem



Three balls object table





Chotest Technology Inc.

China Office Add:

2F&5F, Building B1, Zhiyuan, Xueyuan Road, Xili, Nanshan, Shenzhen, China

US Office Add:

1600 wyatt Drive, Suite 6, Santa Clara, CA 95054, US

Factory Add: 1F&7F, Building No.7, HKC Industry Park, Shiyan, Baoan, Shenzhen, China

Tel: +86-755-83318988-227 Fax: +86-755-83312849 E-mail: sales@chotest.com

Please visit our website for more information

WWW.CHOTEST.COM



WEBSITE

NOTE:CHOTEST HAS MADE CONSIDERABLE EFFORTS TO ENSURE THE CONTENT OF THIS DOCUMENT IS CORRECT AT THE DATE OF PUBLICATION BUT MAKES NO WARRANTIES OR REPRESENTATIONS REGARDING THE CONTENT.

Issued: January, 2024